

Idaho Transportation Department

Monthly WIM Distribution for Sep-2017

Site names: 00185
 County: Idaho
 Funct Class: R Principal Arterial - Other
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	308	262	1	7	4	2	7	20	15	1	2	15	0
	Flex	.00	.00	.00	.88	.41	.32	.55	.33	1.04	.47	.04	1.00	1.06	0.00
	Rigid	.00	.00	.00	1.40	.41	.48	.60	.34	1.66	1.27	.05	1.33	1.84	0.00
	GVW	2.4	4.6	3.6	37.3	20.3	28.7	27.2	23.5	59.7	82.8	22.7	63.4	83.6	0.0
E	Num	1	153	130	1	3	2	2	3	10	7	1	2	7	0
	Flex	.00	.00	.00	1.12	.39	.39	.37	.33	1.39	.54	.05	.99	.65	0.00
	Rigid	.00	.00	.00	1.80	.39	.58	.40	.34	2.25	1.41	.06	1.13	.97	0.00
	GVW	2.3	4.7	3.5	47.6	19.7	31.8	25.5	23.4	66.3	82.0	27.7	59.8	60.3	0.0
W	Num	2	155	131	1	4	3	2	4	10	9	1	2	8	0
	Flex	.00	.00	.00	.83	.43	.31	.65	.32	.64	.43	.03	1.94	1.29	0.00
	Rigid	.00	.00	.00	1.24	.44	.46	.69	.33	1.00	1.21	.04	3.21	2.41	0.00
	GVW	2.3	4.5	3.7	32.5	21.3	28.6	27.0	23.5	51.5	86.9	20.5	90.7	102.3	0.0
E Lane1	Num	1	153	130	1	3	2	2	3	10	7	1	2	7	0
	Flex	.00	.00	.00	1.12	.39	.39	.37	.33	1.39	.54	.05	.99	.65	0.00
	Rigid	.00	.00	.00	1.80	.39	.58	.40	.34	2.25	1.41	.06	1.13	.97	0.00
	GVW	2.3	4.7	3.5	47.6	19.7	31.8	25.5	23.4	66.3	82.0	27.7	59.8	60.3	0.0
W Lane1	Num	2	155	131	1	4	3	2	4	10	9	1	2	8	0
	Flex	.00	.00	.00	.83	.43	.31	.65	.32	.64	.43	.03	1.94	1.29	0.00
	Rigid	.00	.00	.00	1.24	.44	.46	.69	.33	1.00	1.21	.04	3.21	2.41	0.00
	GVW	2.3	4.5	3.7	32.5	21.3	28.6	27.0	23.5	51.5	86.9	20.5	90.7	102.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Sep-2017

Site names: 00185
 County: Idaho
 Funct Class: R Principal Arterial - Other
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9