

Idaho Transportation Department

Monthly WIM Distribution for Mar-2019

Site names: 00185
 County: Idaho
 Funct Class: R Principal Arterial - Other
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	162	133	1	3	10	1	4	14	24	1	1	7	0
	Flex	.00	.00	.00	.57	.64	.92	.56	.24	.92	.74	.88	.30	1.13	0.00
	Rigid	.00	.00	.00	.64	.66	1.18	.79	.33	1.33	1.64	1.02	.32	1.83	0.00
	GVW	2.3	4.0	4.2	25.1	21.8	34.8	33.9	21.2	51.0	75.3	37.0	29.4	73.1	0.0
E	Num	1	83	66	1	2	5	1	2	8	11	0	1	4	0
	Flex	.00	.00	.00	.46	.58	1.28	.78	.07	.99	.67	0.00	.30	.73	0.00
	Rigid	.00	.00	.00	.45	.61	1.66	.79	.10	1.48	1.34	0.00	.32	.95	0.00
	GVW	2.0	3.8	4.0	17.2	21.4	36.9	28.7	18.2	51.8	55.6	0.0	29.4	43.2	0.0
W	Num	2	79	66	1	2	5	1	2	6	13	1	0	4	0
	Flex	.00	.00	.00	.88	.56	.59	.52	.54	.74	.80	.88	0.00	1.25	0.00
	Rigid	.00	.00	.00	1.03	.57	.74	1.12	.71	1.01	1.93	1.02	0.00	2.27	0.00
	GVW	2.7	4.2	4.4	34.0	20.1	33.4	46.9	26.5	47.8	93.7	37.0	0.0	99.9	0.0
E Lane1	Num	1	83	66	1	2	5	1	2	8	11	0	1	4	0
	Flex	.00	.00	.00	.46	.58	1.28	.78	.07	.99	.67	0.00	.30	.73	0.00
	Rigid	.00	.00	.00	.45	.61	1.66	.79	.10	1.48	1.34	0.00	.32	.95	0.00
	GVW	2.0	3.8	4.0	17.2	21.4	36.9	28.7	18.2	51.8	55.6	0.0	29.4	43.2	0.0
W Lane1	Num	2	79	66	1	2	5	1	2	6	13	1	0	4	0
	Flex	.00	.00	.00	.88	.56	.59	.52	.54	.74	.80	.88	0.00	1.25	0.00
	Rigid	.00	.00	.00	1.03	.57	.74	1.12	.71	1.01	1.93	1.02	0.00	2.27	0.00
	GVW	2.7	4.2	4.4	34.0	20.1	33.4	46.9	26.5	47.8	93.7	37.0	0.0	99.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2019

Site names: 00185
 County: Idaho
 Funct Class: R Principal Arterial - Other
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9