

Idaho Transportation Department

Monthly WIM Distribution for May-2019

Site names: 00185
 County: Idaho
 Funct Class: R Principal Arterial - Other
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	350	259	1	6	3	2	10	22	20	1	1	8	0
	Flex	.00	.00	.00	.52	.46	.39	.64	.50	1.75	.78	.09	.98	1.02	0.00
	Rigid	.00	.00	.00	.64	.49	.50	.69	.67	2.73	1.96	.08	1.09	1.83	0.00
	GVW	2.0	3.8	4.2	29.8	18.1	22.6	28.6	22.5	54.6	74.6	24.6	46.1	66.4	0.0
E	Num	1	173	127	1	3	2	1	5	13	10	1	1	4	0
	Flex	.00	.00	.00	.41	.54	.41	.21	.43	1.98	.53	.09	.98	.52	0.00
	Rigid	.00	.00	.00	.57	.57	.52	.20	.49	3.21	1.10	.08	1.09	.66	0.00
	GVW	1.9	3.6	4.0	35.0	17.8	21.9	19.1	16.9	58.3	59.2	25.0	45.8	37.3	0.0
W	Num	2	176	132	1	3	2	2	5	9	10	2	1	4	0
	Flex	.00	.00	.00	.63	.35	.76	.99	.39	1.47	.89	.08	.11	1.55	0.00
	Rigid	.00	.00	.00	.70	.36	1.09	1.08	.58	2.23	2.50	.08	.13	3.19	0.00
	GVW	1.9	4.0	4.5	24.5	17.6	31.6	34.2	25.8	48.1	89.4	22.2	42.3	94.3	0.0
E Lane1	Num	1	173	127	1	3	2	1	5	13	10	1	1	4	0
	Flex	.00	.00	.00	.41	.54	.41	.21	.43	1.98	.53	.09	.98	.52	0.00
	Rigid	.00	.00	.00	.57	.57	.52	.20	.49	3.21	1.10	.08	1.09	.66	0.00
	GVW	1.9	3.6	4.0	35.0	17.8	21.9	19.1	16.9	58.3	59.2	25.0	45.8	37.3	0.0
W Lane1	Num	2	176	132	1	3	2	2	5	9	10	2	1	4	0
	Flex	.00	.00	.00	.63	.35	.76	.99	.39	1.47	.89	.08	.11	1.55	0.00
	Rigid	.00	.00	.00	.70	.36	1.09	1.08	.58	2.23	2.50	.08	.13	3.19	0.00
	GVW	1.9	4.0	4.5	24.5	17.6	31.6	34.2	25.8	48.1	89.4	22.2	42.3	94.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2019

Site names: 00185
 County: Idaho
 Funct Class: R Principal Arterial - Other
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9