

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2019

Site names: 00185  
 County: Idaho  
 Funct Class: R Principal Arterial - Other  
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	217	204	1	5	12	2	7	18	22	2	1	10	0
	Flex	.00	.00	.00	1.16	.26	.69	.53	.20	1.05	.56	2.30	.46	.64	0.00
	Rigid	.00	.00	.00	1.45	.25	.97	.56	.25	1.54	1.31	2.90	.49	1.07	0.00
	GVW	2.4	3.9	4.2	42.4	17.6	33.0	28.8	24.0	53.6	73.7	38.2	43.1	67.8	0.0
E	Num	2	107	100	1	3	7	1	3	11	10	1	1	5	0
	Flex	.00	.00	.00	.87	.20	.77	.81	.18	1.38	.62	.23	.40	.30	0.00
	Rigid	.00	.00	.00	.85	.20	1.12	.80	.19	2.02	1.30	.47	.40	.39	0.00
	GVW	2.3	3.8	3.9	27.5	16.2	34.2	31.0	21.1	57.3	60.1	34.5	40.4	36.4	0.0
W	Num	2	111	104	1	3	5	2	4	7	12	2	1	5	0
	Flex	.00	.00	.00	1.23	.30	.75	.44	.21	.50	.49	4.38	1.00	.83	0.00
	Rigid	.00	.00	.00	1.56	.29	1.04	.49	.28	.74	1.28	5.31	1.32	1.50	0.00
	GVW	2.6	4.0	4.5	44.7	17.9	33.6	30.0	26.7	47.5	85.0	43.2	75.2	90.0	0.0
E Lane1	Num	2	107	100	1	3	7	1	3	11	10	1	1	5	0
	Flex	.00	.00	.00	.87	.20	.77	.81	.18	1.38	.62	.23	.40	.30	0.00
	Rigid	.00	.00	.00	.85	.20	1.12	.80	.19	2.02	1.30	.47	.40	.39	0.00
	GVW	2.3	3.8	3.9	27.5	16.2	34.2	31.0	21.1	57.3	60.1	34.5	40.4	36.4	0.0
W Lane1	Num	2	111	104	1	3	5	2	4	7	12	2	1	5	0
	Flex	.00	.00	.00	1.23	.30	.75	.44	.21	.50	.49	4.38	1.00	.83	0.00
	Rigid	.00	.00	.00	1.56	.29	1.04	.49	.28	.74	1.28	5.31	1.32	1.50	0.00
	GVW	2.6	4.0	4.5	44.7	17.9	33.6	30.0	26.7	47.5	85.0	43.2	75.2	90.0	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2019

Site names: 00185  
 County: Idaho  
 Funct Class: R Principal Arterial - Other  
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9