

Idaho Transportation Department

Monthly WIM Distribution for May-2021

Site names: 00185
 County: Idaho
 Funct Class: R Principal Arterial - Other
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 8

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	582	595	491	1	9	3	1	13	9	9	1	0	5	0
	Flex	.06	.00	.00	3.31	.69	.46	.90	.83	2.67	.64	.07	0.00	.88	0.00
	Rigid	.09	.00	.00	3.64	.72	.57	.90	.93	3.88	1.27	.07	0.00	1.29	0.00
	GVW	7.4	4.1	4.2	36.6	21.8	28.2	27.8	19.1	64.7	58.9	25.2	0.0	72.1	0.0
E	Num	281	294	249	1	5	2	1	7	5	6	1	0	2	0
	Flex	.08	.00	.00	3.31	1.05	.47	.82	.83	3.74	1.25	.05	0.00	.59	0.00
	Rigid	.12	.00	.00	3.64	1.12	.74	.81	.93	5.68	2.46	.06	0.00	.65	0.00
	GVW	7.5	4.0	3.7	36.6	25.3	26.9	23.2	18.9	77.0	75.0	29.0	0.0	51.7	0.0
W	Num	316	302	242	0	4	2	2	6	4	4	1	0	3	0
	Flex	.04	.00	.00	0.00	.33	.52	.94	.83	1.16	.17	.08	0.00	1.08	0.00
	Rigid	.06	.00	.00	0.00	.32	.60	.94	.93	1.46	.35	.07	0.00	1.72	0.00
	GVW	7.4	4.2	4.6	0.0	18.0	31.3	30.0	19.2	50.6	51.6	21.4	0.0	84.6	0.0
E Lane1	Num	281	294	249	1	5	2	1	7	5	6	1	0	2	0
	Flex	.08	.00	.00	3.31	1.05	.47	.82	.83	3.74	1.25	.05	0.00	.59	0.00
	Rigid	.12	.00	.00	3.64	1.12	.74	.81	.93	5.68	2.46	.06	0.00	.65	0.00
	GVW	7.5	4.0	3.7	36.6	25.3	26.9	23.2	18.9	77.0	75.0	29.0	0.0	51.7	0.0
W Lane1	Num	316	302	242	0	4	2	2	6	4	4	1	0	3	0
	Flex	.04	.00	.00	0.00	.33	.52	.94	.83	1.16	.17	.08	0.00	1.08	0.00
	Rigid	.06	.00	.00	0.00	.32	.60	.94	.93	1.46	.35	.07	0.00	1.72	0.00
	GVW	7.4	4.2	4.6	0.0	18.0	31.3	30.0	19.2	50.6	51.6	21.4	0.0	84.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2021

Site names: 00185
 County: Idaho
 Funct Class: R Principal Arterial - Other
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 8

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9