

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2021

Site names: 00185  
 County: Idaho  
 Funct Class: R Principal Arterial - Other  
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 8

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	6	458	387	1	11	6	2	16	23	20	1	1	6	0
	Flex	.00	.00	.00	.41	.41	.33	.62	.42	1.28	.47	.05	.43	.92	0.00
	Rigid	.00	.00	.00	.51	.42	.44	.63	.46	1.93	.95	.06	.45	1.48	0.00
	GVW	1.2	3.8	4.4	29.3	16.5	24.4	24.3	18.2	50.6	61.5	22.8	42.1	64.8	0.0
E	Num	3	225	187	1	5	3	1	8	12	10	1	1	3	0
	Flex	.00	.00	.00	.46	.52	.22	.66	.50	1.78	.62	.03	.42	.58	0.00
	Rigid	.00	.00	.00	.57	.55	.31	.68	.57	2.80	1.08	.05	.43	.83	0.00
	GVW	1.3	3.9	4.0	27.9	17.6	23.1	23.4	19.3	60.0	58.9	21.7	40.7	41.0	0.0
W	Num	3	233	200	1	5	4	1	8	11	10	1	1	3	0
	Flex	.00	.00	.00	.40	.26	.47	.81	.25	.78	.34	.10	.46	.90	0.00
	Rigid	.00	.00	.00	.48	.27	.64	.84	.25	1.05	.83	.10	.59	1.55	0.00
	GVW	1.1	3.7	4.7	29.8	15.1	27.8	26.3	16.5	40.4	63.6	23.7	62.2	82.9	0.0
E Lane1	Num	3	225	187	1	5	3	1	8	12	10	1	1	3	0
	Flex	.00	.00	.00	.46	.52	.22	.66	.50	1.78	.62	.03	.42	.58	0.00
	Rigid	.00	.00	.00	.57	.55	.31	.68	.57	2.80	1.08	.05	.43	.83	0.00
	GVW	1.3	3.9	4.0	27.9	17.6	23.1	23.4	19.3	60.0	58.9	21.7	40.7	41.0	0.0
W Lane1	Num	3	233	200	1	5	4	1	8	11	10	1	1	3	0
	Flex	.00	.00	.00	.40	.26	.47	.81	.25	.78	.34	.10	.46	.90	0.00
	Rigid	.00	.00	.00	.48	.27	.64	.84	.25	1.05	.83	.10	.59	1.55	0.00
	GVW	1.1	3.7	4.7	29.8	15.1	27.8	26.3	16.5	40.4	63.6	23.7	62.2	82.9	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2021

Site names: 00185  
 County: Idaho  
 Funct Class: R Principal Arterial - Other  
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 8

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9