

Idaho Transportation Department

Monthly WIM Distribution for Jul-2022

Site names: 00185
 County: Idaho
 Funct Class: R Principal Arterial - Other
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 8

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	8	439	385	1	10	6	2	15	22	19	1	1	5	0
	Flex	.00	.00	.00	.59	.20	.29	.22	.20	.77	.33	.08	.25	1.01	0.00
	Rigid	.00	.00	.00	.91	.19	.40	.26	.21	1.17	.66	.08	.25	1.63	0.00
	GVW	1.3	3.8	4.5	26.8	14.8	24.2	21.6	17.1	49.7	59.2	23.6	38.0	71.2	0.0
E	Num	3	208	184	1	5	3	1	7	12	10	1	1	2	0
	Flex	.00	.00	.00	.28	.30	.28	.24	.19	1.07	.43	.14	.25	.98	0.00
	Rigid	.00	.00	.00	.47	.29	.37	.25	.20	1.67	.76	.15	.25	1.46	0.00
	GVW	1.4	4.0	4.1	18.9	16.6	24.9	18.8	17.7	57.7	57.0	27.0	38.0	56.1	0.0
W	Num	5	231	201	1	6	3	2	8	10	9	1	0	3	0
	Flex	.00	.00	.00	1.04	.15	.29	.17	.21	.44	.23	.04	0.00	.79	0.00
	Rigid	.00	.00	.00	1.54	.14	.40	.22	.23	.59	.58	.04	0.00	1.36	0.00
	GVW	1.2	3.6	4.9	38.9	14.1	22.9	22.4	16.5	40.2	61.9	21.2	0.0	75.0	0.0
E Lane1	Num	3	208	184	1	5	3	1	7	12	10	1	1	2	0
	Flex	.00	.00	.00	.28	.30	.28	.24	.19	1.07	.43	.14	.25	.98	0.00
	Rigid	.00	.00	.00	.47	.29	.37	.25	.20	1.67	.76	.15	.25	1.46	0.00
	GVW	1.4	4.0	4.1	18.9	16.6	24.9	18.8	17.7	57.7	57.0	27.0	38.0	56.1	0.0
W Lane1	Num	5	231	201	1	6	3	2	8	10	9	1	0	3	0
	Flex	.00	.00	.00	1.04	.15	.29	.17	.21	.44	.23	.04	0.00	.79	0.00
	Rigid	.00	.00	.00	1.54	.14	.40	.22	.23	.59	.58	.04	0.00	1.36	0.00
	GVW	1.2	3.6	4.9	38.9	14.1	22.9	22.4	16.5	40.2	61.9	21.2	0.0	75.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2022

Site names: 00185
 County: Idaho
 Funct Class: R Principal Arterial - Other
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 8

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9