

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2022

Site names: 00185  
 County: Idaho  
 Funct Class: R Principal Arterial - Other  
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 8

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	9	352	359	1	9	5	3	12	24	26	2	1	5	0
	Flex	.00	.00	.00	.08	.22	.28	.31	.27	.84	.38	.20	.60	1.30	0.00
	Rigid	.00	.00	.00	.08	.22	.37	.47	.30	1.24	.79	.24	.62	2.03	0.00
	GVW	1.1	3.8	4.5	12.6	15.4	24.7	30.8	18.1	48.9	59.9	22.4	45.6	74.2	0.0
E	Num	2	167	173	1	4	3	2	6	13	13	1	1	3	0
	Flex	.00	.00	.00	.02	.23	.26	.31	.47	1.10	.47	.18	.68	1.94	0.00
	Rigid	.00	.00	.00	.02	.22	.36	.37	.51	1.66	.86	.32	.70	2.99	0.00
	GVW	1.6	3.9	4.2	8.7	15.4	24.7	27.0	20.0	54.0	53.5	19.9	47.8	69.0	0.0
W	Num	8	184	186	1	5	3	2	6	11	13	1	1	3	0
	Flex	.00	.00	.00	.13	.24	.32	.31	.17	.42	.29	.20	.03	.85	0.00
	Rigid	.00	.00	.00	.13	.24	.46	.60	.20	.57	.73	.19	.03	1.34	0.00
	GVW	1.0	3.8	4.8	20.4	15.4	24.3	36.8	17.5	39.8	66.1	23.2	24.5	78.8	0.0
E Lane1	Num	2	167	173	1	4	3	2	6	13	13	1	1	3	0
	Flex	.00	.00	.00	.02	.23	.26	.31	.47	1.10	.47	.18	.68	1.94	0.00
	Rigid	.00	.00	.00	.02	.22	.36	.37	.51	1.66	.86	.32	.70	2.99	0.00
	GVW	1.6	3.9	4.2	8.7	15.4	24.7	27.0	20.0	54.0	53.5	19.9	47.8	69.0	0.0
W Lane1	Num	8	184	186	1	5	3	2	6	11	13	1	1	3	0
	Flex	.00	.00	.00	.13	.24	.32	.31	.17	.42	.29	.20	.03	.85	0.00
	Rigid	.00	.00	.00	.13	.24	.46	.60	.20	.57	.73	.19	.03	1.34	0.00
	GVW	1.0	3.8	4.8	20.4	15.4	24.3	36.8	17.5	39.8	66.1	23.2	24.5	78.8	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2022

Site names: 00185  
 County: Idaho  
 Funct Class: R Principal Arterial - Other  
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 8

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9