

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2023

Site names: 00185  
 County: Idaho  
 Funct Class: R Principal Arterial - Other  
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10  
 Daily Factor Grp: 5  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 8

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	244	255	1	5	9	1	8	19	36	2	1	5	0
	Flex	.00	.00	.00	.25	.21	.47	.52	.20	.87	.54	.25	1.75	.82	0.00
	Rigid	.00	.00	.00	.38	.20	.68	.54	.26	1.29	1.15	.35	1.95	1.39	0.00
	GVW	1.9	3.9	4.4	23.2	15.2	27.8	24.0	20.7	48.5	63.8	27.4	56.4	73.2	0.0
E	Num	2	115	121	1	3	3	1	4	10	18	1	1	3	0
	Flex	.00	.00	.00	.25	.34	.79	.56	.30	1.33	.78	.34	.72	.95	0.00
	Rigid	.00	.00	.00	.38	.34	1.27	.58	.39	2.00	1.60	.35	.74	1.40	0.00
	GVW	2.2	4.0	3.9	23.2	16.9	32.6	24.8	24.5	57.9	63.1	27.6	52.0	57.9	0.0
W	Num	2	129	134	0	3	6	1	4	8	18	2	2	3	0
	Flex	.00	.00	.00	0.00	.13	.28	.20	.06	.35	.30	.22	6.57	.70	0.00
	Rigid	.00	.00	.00	0.00	.12	.34	.22	.09	.46	.69	.34	7.62	1.35	0.00
	GVW	1.2	3.8	4.7	0.0	14.3	25.6	20.7	17.2	37.6	64.1	27.1	72.4	83.9	0.0
E Lane1	Num	2	115	121	1	3	3	1	4	10	18	1	1	3	0
	Flex	.00	.00	.00	.25	.34	.79	.56	.30	1.33	.78	.34	.72	.95	0.00
	Rigid	.00	.00	.00	.38	.34	1.27	.58	.39	2.00	1.60	.35	.74	1.40	0.00
	GVW	2.2	4.0	3.9	23.2	16.9	32.6	24.8	24.5	57.9	63.1	27.6	52.0	57.9	0.0
W Lane1	Num	2	129	134	0	3	6	1	4	8	18	2	2	3	0
	Flex	.00	.00	.00	0.00	.13	.28	.20	.06	.35	.30	.22	6.57	.70	0.00
	Rigid	.00	.00	.00	0.00	.12	.34	.22	.09	.46	.69	.34	7.62	1.35	0.00
	GVW	1.2	3.8	4.7	0.0	14.3	25.6	20.7	17.2	37.6	64.1	27.1	72.4	83.9	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2023

Site names: 00185  
 County: Idaho  
 Funct Class: R Principal Arterial - Other  
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10  
 Daily Factor Grp: 5  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 8

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9