

Idaho Transportation Department

Monthly WIM Distribution for May-2017

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	9	1,996	1,084	42	98	14	2	12	783	17	4	2	14	0
	Flex	.00	.00	.00	.29	.09	.16	.27	.16	.46	.27	.54	.31	.51	0.00
	Rigid	.00	.00	.00	.34	.09	.22	.46	.17	.77	.56	.51	.32	.63	0.00
	GVW	3.4	3.2	6.0	26.0	17.4	22.5	39.7	25.3	52.7	58.8	45.6	46.2	58.6	0.0
N	Num	5	1,042	550	21	55	6	2	7	360	9	2	2	8	0
	Flex	.00	.00	.00	.26	.09	.12	.16	.18	.38	.21	.77	.35	.48	0.00
	Rigid	.00	.00	.00	.31	.09	.15	.39	.18	.62	.41	.72	.35	.58	0.00
	GVW	4.0	3.1	6.0	26.4	17.4	20.3	41.6	25.8	50.4	52.6	52.4	48.0	57.3	0.0
S	Num	4	954	534	21	43	8	1	5	423	8	2	2	6	0
	Flex	.00	.00	.00	.32	.10	.19	.27	.14	.52	.34	.35	.32	.55	0.00
	Rigid	.00	.00	.00	.36	.09	.29	.46	.15	.91	.71	.33	.33	.70	0.00
	GVW	2.4	3.3	6.0	25.7	17.3	24.6	39.7	23.9	54.7	64.7	40.0	46.2	60.9	0.0
N Lane1	Num	5	1,042	550	21	55	6	2	7	360	9	2	2	8	0
	Flex	.00	.00	.00	.26	.09	.12	.16	.18	.38	.21	.77	.35	.48	0.00
	Rigid	.00	.00	.00	.31	.09	.15	.39	.18	.62	.41	.72	.35	.58	0.00
	GVW	4.0	3.1	6.0	26.4	17.4	20.3	41.6	25.8	50.4	52.6	52.4	48.0	57.3	0.0
S Lane1	Num	4	954	534	21	43	8	1	5	423	8	2	2	6	0
	Flex	.00	.00	.00	.32	.10	.19	.27	.14	.52	.34	.35	.32	.55	0.00
	Rigid	.00	.00	.00	.36	.09	.29	.46	.15	.91	.71	.33	.33	.70	0.00
	GVW	2.4	3.3	6.0	25.7	17.3	24.6	39.7	23.9	54.7	64.7	40.0	46.2	60.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2017

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9