

Idaho Transportation Department

Monthly WIM Distribution for Jun-2017

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	19	1,793	1,035	50	122	40	2	14	655	16	3	2	10	0
	Flex	.00	.00	.00	.27	.09	.19	.22	.18	.44	.30	.47	.30	.50	0.00
	Rigid	.00	.00	.00	.32	.09	.29	.48	.18	.75	.63	.44	.30	.60	0.00
	GVW	3.8	3.2	6.1	24.7	16.7	25.0	43.2	25.8	52.3	58.3	43.4	48.2	59.3	0.0
N	Num	9	938	580	25	66	12	1	8	313	8	2	1	6	0
	Flex	.00	.00	.00	.25	.08	.13	.14	.16	.38	.23	.67	.30	.55	0.00
	Rigid	.00	.00	.00	.30	.08	.17	.30	.17	.62	.47	.64	.30	.65	0.00
	GVW	3.4	3.1	5.9	25.1	16.6	20.9	38.4	25.3	50.4	50.8	51.2	46.4	61.6	0.0
S	Num	10	903	509	26	56	28	2	6	352	7	1	2	5	0
	Flex	.00	.00	.00	.29	.10	.21	.26	.19	.51	.38	.27	.26	.51	0.00
	Rigid	.00	.00	.00	.34	.10	.35	.58	.20	.89	.79	.26	.26	.69	0.00
	GVW	3.8	3.4	6.1	24.6	16.8	27.2	45.9	26.4	54.2	65.2	36.5	46.8	60.1	0.0
N Lane1	Num	9	938	580	25	66	12	1	8	313	8	2	1	6	0
	Flex	.00	.00	.00	.25	.08	.13	.14	.16	.38	.23	.67	.30	.55	0.00
	Rigid	.00	.00	.00	.30	.08	.17	.30	.17	.62	.47	.64	.30	.65	0.00
	GVW	3.4	3.1	5.9	25.1	16.6	20.9	38.4	25.3	50.4	50.8	51.2	46.4	61.6	0.0
S Lane1	Num	10	903	509	26	56	28	2	6	352	7	1	2	5	0
	Flex	.00	.00	.00	.29	.10	.21	.26	.19	.51	.38	.27	.26	.51	0.00
	Rigid	.00	.00	.00	.34	.10	.35	.58	.20	.89	.79	.26	.26	.69	0.00
	GVW	3.8	3.4	6.1	24.6	16.8	27.2	45.9	26.4	54.2	65.2	36.5	46.8	60.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2017

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9