

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	34	2,335	1,328	63	132	124	4	13	573	13	3	3	4	0
	Flex	.00	.00	.00	.30	.11	.22	.18	.23	.45	.33	.72	.53	.45	0.00
	Rigid	.00	.00	.00	.37	.11	.35	.40	.25	.77	.67	.69	.53	.65	0.00
	GVW	4.3	3.3	5.9	26.0	17.1	29.0	41.5	28.5	52.5	60.2	48.0	54.5	62.2	0.0
N	Num	14	1,183	626	27	60	39	2	7	273	7	2	2	3	0
	Flex	.00	.00	.00	.25	.10	.15	.15	.21	.37	.26	.79	.59	.40	0.00
	Rigid	.00	.00	.00	.30	.10	.21	.34	.22	.60	.53	.74	.59	.55	0.00
	GVW	4.0	3.2	5.9	25.1	16.9	24.4	40.3	28.3	49.1	58.1	53.1	58.0	60.2	0.0
S	Num	19	1,152	702	35	72	85	2	6	301	6	2	2	2	0
	Flex	.00	.00	.00	.34	.13	.24	.20	.25	.52	.43	.57	.59	.64	0.00
	Rigid	.00	.00	.00	.42	.12	.40	.43	.28	.92	.90	.54	.60	.92	0.00
	GVW	4.5	3.4	6.0	26.6	17.3	30.6	42.4	28.2	55.6	64.9	42.3	54.2	66.4	0.0
N Lane1	Num	14	1,183	626	27	60	39	2	7	273	7	2	2	3	0
	Flex	.00	.00	.00	.25	.10	.15	.15	.21	.37	.26	.79	.59	.40	0.00
	Rigid	.00	.00	.00	.30	.10	.21	.34	.22	.60	.53	.74	.59	.55	0.00
	GVW	4.0	3.2	5.9	25.1	16.9	24.4	40.3	28.3	49.1	58.1	53.1	58.0	60.2	0.0
S Lane1	Num	19	1,152	702	35	72	85	2	6	301	6	2	2	2	0
	Flex	.00	.00	.00	.34	.13	.24	.20	.25	.52	.43	.57	.59	.64	0.00
	Rigid	.00	.00	.00	.42	.12	.40	.43	.28	.92	.90	.54	.60	.92	0.00
	GVW	4.5	3.4	6.0	26.6	17.3	30.6	42.4	28.2	55.6	64.9	42.3	54.2	66.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9