

Idaho Transportation Department

Monthly WIM Distribution for Jan-2019

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	1,485	868	14	32	10	7	36	675	18	8	4	21	0
	Flex	.00	.00	.00	.31	.27	.32	.30	.20	.62	.46	.38	.41	.78	0.00
	Rigid	.00	.00	.00	.46	.27	.43	.32	.21	1.07	.91	.40	.43	1.19	0.00
	GVW	2.9	4.1	4.7	33.1	17.8	27.0	23.8	24.0	56.9	66.4	37.5	50.0	70.4	0.0
N	Num	1	754	413	7	13	6	2	17	298	8	4	2	10	0
	Flex	.00	.00	.00	.34	.23	.29	.29	.17	.51	.59	.46	.47	.64	0.00
	Rigid	.00	.00	.00	.52	.23	.38	.30	.18	.85	1.02	.48	.48	.91	0.00
	GVW	1.9	4.1	4.5	34.5	17.3	26.0	23.6	25.0	52.8	65.7	43.2	52.7	68.3	0.0
S	Num	1	732	455	7	19	5	5	19	377	10	4	2	11	0
	Flex	.00	.00	.00	.27	.29	.37	.28	.23	.71	.44	.32	.35	.93	0.00
	Rigid	.00	.00	.00	.41	.29	.51	.30	.24	1.24	.92	.32	.37	1.53	0.00
	GVW	3.2	4.2	4.9	31.9	18.1	28.6	23.2	23.1	60.2	67.9	33.0	47.4	74.2	0.0
N Lane1	Num	1	754	413	7	13	6	2	17	298	8	4	2	10	0
	Flex	.00	.00	.00	.34	.23	.29	.29	.17	.51	.59	.46	.47	.64	0.00
	Rigid	.00	.00	.00	.52	.23	.38	.30	.18	.85	1.02	.48	.48	.91	0.00
	GVW	1.9	4.1	4.5	34.5	17.3	26.0	23.6	25.0	52.8	65.7	43.2	52.7	68.3	0.0
S Lane1	Num	1	732	455	7	19	5	5	19	377	10	4	2	11	0
	Flex	.00	.00	.00	.27	.29	.37	.28	.23	.71	.44	.32	.35	.93	0.00
	Rigid	.00	.00	.00	.41	.29	.51	.30	.24	1.24	.92	.32	.37	1.53	0.00
	GVW	3.2	4.2	4.9	31.9	18.1	28.6	23.2	23.1	60.2	67.9	33.0	47.4	74.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2019

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9