

Idaho Transportation Department

Monthly WIM Distribution for Feb-2019

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	1,337	792	13	32	11	5	29	594	14	9	4	19	0
	Flex	.00	.00	.00	.33	.26	.37	.27	.18	.62	.41	.42	.34	.60	0.00
	Rigid	.00	.00	.00	.49	.25	.55	.27	.18	1.08	.88	.43	.36	.95	0.00
	GVW	2.4	4.1	4.7	33.0	17.4	27.8	22.8	23.1	57.0	67.9	38.8	48.9	67.0	0.0
N	Num	2	673	388	7	14	6	3	17	263	7	5	2	10	0
	Flex	.00	.00	.00	.34	.21	.38	.28	.18	.52	.37	.43	.39	.55	0.00
	Rigid	.00	.00	.00	.52	.20	.56	.28	.18	.87	.81	.45	.40	.86	0.00
	GVW	1.9	4.1	4.6	33.8	17.0	26.8	24.5	23.3	53.2	69.0	40.0	51.9	66.7	0.0
S	Num	1	665	405	7	18	5	2	13	330	7	4	2	9	0
	Flex	.00	.00	.00	.30	.29	.40	.23	.18	.70	.46	.37	.32	.65	0.00
	Rigid	.00	.00	.00	.45	.28	.60	.24	.18	1.25	.96	.36	.36	1.02	0.00
	GVW	3.3	4.1	4.9	32.1	17.7	29.5	20.7	22.8	60.0	67.5	35.9	47.5	67.0	0.0
N Lane1	Num	2	673	388	7	14	6	3	17	263	7	5	2	10	0
	Flex	.00	.00	.00	.34	.21	.38	.28	.18	.52	.37	.43	.39	.55	0.00
	Rigid	.00	.00	.00	.52	.20	.56	.28	.18	.87	.81	.45	.40	.86	0.00
	GVW	1.9	4.1	4.6	33.8	17.0	26.8	24.5	23.3	53.2	69.0	40.0	51.9	66.7	0.0
S Lane1	Num	1	665	405	7	18	5	2	13	330	7	4	2	9	0
	Flex	.00	.00	.00	.30	.29	.40	.23	.18	.70	.46	.37	.32	.65	0.00
	Rigid	.00	.00	.00	.45	.28	.60	.24	.18	1.25	.96	.36	.36	1.02	0.00
	GVW	3.3	4.1	4.9	32.1	17.7	29.5	20.7	22.8	60.0	67.5	35.9	47.5	67.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2019

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9