

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2019

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	2,303	1,271	18	66	12	14	74	815	23	7	2	24	0
	Flex	.00	.00	.00	.50	.29	.23	.41	.29	.74	.55	.56	.48	.93	0.00
	Rigid	.00	.00	.00	.77	.29	.31	.43	.31	1.29	1.17	.55	.51	1.32	0.00
	GVW	1.6	4.0	4.9	35.4	17.3	24.7	23.8	21.7	58.1	70.7	37.0	50.2	66.8	0.0
N	Num	1	1,220	649	9	32	7	5	43	386	12	4	1	12	0
	Flex	.00	.00	.00	.66	.31	.25	.56	.37	.80	.60	.70	.47	.90	0.00
	Rigid	.00	.00	.00	1.03	.31	.35	.57	.39	1.40	1.24	.69	.50	1.28	0.00
	GVW	1.4	4.1	4.9	38.8	17.9	25.7	26.1	22.6	59.0	68.7	40.1	49.0	60.5	0.0
S	Num	1	1,083	622	8	34	6	9	31	430	11	4	1	12	0
	Flex	.00	.00	.00	.31	.27	.20	.32	.20	.68	.55	.41	.45	.96	0.00
	Rigid	.00	.00	.00	.46	.26	.27	.33	.20	1.20	1.25	.39	.51	1.34	0.00
	GVW	1.6	3.9	5.0	31.6	16.7	23.4	22.2	20.3	57.3	74.8	35.2	52.0	73.6	0.0
N Lane1	Num	1	1,220	649	9	32	7	5	43	386	12	4	1	12	0
	Flex	.00	.00	.00	.66	.31	.25	.56	.37	.80	.60	.70	.47	.90	0.00
	Rigid	.00	.00	.00	1.03	.31	.35	.57	.39	1.40	1.24	.69	.50	1.28	0.00
	GVW	1.4	4.1	4.9	38.8	17.9	25.7	26.1	22.6	59.0	68.7	40.1	49.0	60.5	0.0
S Lane1	Num	1	1,083	622	8	34	6	9	31	430	11	4	1	12	0
	Flex	.00	.00	.00	.31	.27	.20	.32	.20	.68	.55	.41	.45	.96	0.00
	Rigid	.00	.00	.00	.46	.26	.27	.33	.20	1.20	1.25	.39	.51	1.34	0.00
	GVW	1.6	3.9	5.0	31.6	16.7	23.4	22.2	20.3	57.3	74.8	35.2	52.0	73.6	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2019

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9