

Idaho Transportation Department

Monthly WIM Distribution for Aug-2019

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	2,232	1,240	14	63	9	12	62	703	21	7	3	31	0
	Flex	.00	.00	.00	.47	.31	.31	.53	.34	.79	.61	.63	.59	1.11	0.00
	Rigid	.00	.00	.00	.74	.31	.42	.56	.35	1.41	1.31	.63	.64	1.66	0.00
	GVW	1.6	4.0	4.9	34.6	17.6	25.7	24.1	22.5	58.1	70.9	38.6	50.3	72.1	0.0
N	Num	2	1,121	597	8	28	5	5	29	323	10	3	2	14	0
	Flex	.00	.00	.00	.59	.40	.32	.63	.38	.89	.67	.93	.91	1.27	0.00
	Rigid	.00	.00	.00	.95	.40	.42	.68	.40	1.56	1.46	.92	.96	1.86	0.00
	GVW	1.5	4.1	4.7	37.1	19.0	25.8	25.1	23.5	57.4	70.1	42.6	55.8	66.8	0.0
S	Num	2	1,111	643	7	35	5	7	33	381	11	4	2	16	0
	Flex	.00	.00	.00	.32	.25	.30	.37	.30	.72	.58	.44	.35	1.02	0.00
	Rigid	.00	.00	.00	.48	.25	.42	.38	.31	1.28	1.20	.43	.40	1.52	0.00
	GVW	1.6	3.9	5.0	31.5	16.6	25.8	23.5	21.5	58.6	71.5	36.7	44.2	76.8	0.0
N Lane1	Num	2	1,121	597	8	28	5	5	29	323	10	3	2	14	0
	Flex	.00	.00	.00	.59	.40	.32	.63	.38	.89	.67	.93	.91	1.27	0.00
	Rigid	.00	.00	.00	.95	.40	.42	.68	.40	1.56	1.46	.92	.96	1.86	0.00
	GVW	1.5	4.1	4.7	37.1	19.0	25.8	25.1	23.5	57.4	70.1	42.6	55.8	66.8	0.0
S Lane1	Num	2	1,111	643	7	35	5	7	33	381	11	4	2	16	0
	Flex	.00	.00	.00	.32	.25	.30	.37	.30	.72	.58	.44	.35	1.02	0.00
	Rigid	.00	.00	.00	.48	.25	.42	.38	.31	1.28	1.20	.43	.40	1.52	0.00
	GVW	1.6	3.9	5.0	31.5	16.6	25.8	23.5	21.5	58.6	71.5	36.7	44.2	76.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Aug-2019

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9