

Idaho Transportation Department

Monthly WIM Distribution for Sep-2019

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	2,010	1,227	12	66	8	11	65	711	16	7	2	30	0
	Flex	.00	.00	.00	.49	.29	.30	.33	.31	.66	.48	.45	.33	.84	0.00
	Rigid	.00	.00	.00	.72	.28	.44	.34	.33	1.15	1.05	.44	.33	1.17	0.00
	GVW	1.1	3.9	5.0	33.9	17.4	24.3	23.0	22.1	56.3	68.7	36.1	43.5	66.7	0.0
N	Num	1	985	565	6	29	5	4	26	327	7	3	2	14	0
	Flex	.00	.00	.00	.62	.33	.36	.32	.27	.67	.70	.72	.43	.94	0.00
	Rigid	.00	.00	.00	.95	.32	.55	.33	.31	1.14	1.56	.70	.44	1.32	0.00
	GVW	.8	4.0	4.8	37.0	18.2	25.3	23.4	22.6	54.9	72.2	43.0	50.4	68.5	0.0
S	Num	1	1,025	663	6	38	3	7	39	384	9	4	2	15	0
	Flex	.00	.00	.00	.35	.26	.17	.32	.33	.65	.35	.29	.24	.74	0.00
	Rigid	.00	.00	.00	.49	.26	.23	.32	.34	1.15	.79	.29	.25	1.02	0.00
	GVW	1.1	3.9	5.1	30.6	16.8	22.5	22.9	21.9	57.6	68.3	32.0	40.0	65.2	0.0
N Lane1	Num	1	985	565	6	29	5	4	26	327	7	3	2	14	0
	Flex	.00	.00	.00	.62	.33	.36	.32	.27	.67	.70	.72	.43	.94	0.00
	Rigid	.00	.00	.00	.95	.32	.55	.33	.31	1.14	1.56	.70	.44	1.32	0.00
	GVW	.8	4.0	4.8	37.0	18.2	25.3	23.4	22.6	54.9	72.2	43.0	50.4	68.5	0.0
S Lane1	Num	1	1,025	663	6	38	3	7	39	384	9	4	2	15	0
	Flex	.00	.00	.00	.35	.26	.17	.32	.33	.65	.35	.29	.24	.74	0.00
	Rigid	.00	.00	.00	.49	.26	.23	.32	.34	1.15	.79	.29	.25	1.02	0.00
	GVW	1.1	3.9	5.1	30.6	16.8	22.5	22.9	21.9	57.6	68.3	32.0	40.0	65.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Sep-2019

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9