

Idaho Transportation Department

Monthly WIM Distribution for Oct-2019

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	1,915	1,220	14	59	10	14	73	768	19	8	3	32	0
	Flex	.00	.00	.00	.39	.24	.24	.32	.31	.59	.47	.35	.49	.70	0.00
	Rigid	.00	.00	.00	.55	.24	.30	.32	.31	1.00	.92	.34	.51	1.00	0.00
	GVW	2.7	4.0	5.0	32.8	17.2	24.2	22.6	22.6	55.5	67.1	34.5	50.5	62.3	0.0
N	Num	1	901	541	8	24	5	4	21	337	9	3	2	15	0
	Flex	.00	.00	.00	.40	.21	.27	.20	.17	.49	.42	.54	.52	.60	0.00
	Rigid	.00	.00	.00	.57	.21	.33	.20	.17	.80	.82	.51	.54	.78	0.00
	GVW	7.1	3.9	4.8	33.4	16.8	24.4	21.5	21.6	51.9	62.6	41.0	55.2	60.1	0.0
S	Num	1	1,014	679	7	35	5	10	52	431	10	5	2	16	0
	Flex	.00	.00	.00	.34	.26	.23	.36	.37	.67	.50	.25	.43	.79	0.00
	Rigid	.00	.00	.00	.47	.26	.29	.37	.37	1.16	1.02	.25	.44	1.21	0.00
	GVW	2.1	4.1	5.1	31.3	17.4	24.4	22.9	23.0	58.3	70.6	31.1	47.5	64.8	0.0
N Lane1	Num	1	901	541	8	24	5	4	21	337	9	3	2	15	0
	Flex	.00	.00	.00	.40	.21	.27	.20	.17	.49	.42	.54	.52	.60	0.00
	Rigid	.00	.00	.00	.57	.21	.33	.20	.17	.80	.82	.51	.54	.78	0.00
	GVW	7.1	3.9	4.8	33.4	16.8	24.4	21.5	21.6	51.9	62.6	41.0	55.2	60.1	0.0
S Lane1	Num	1	1,014	679	7	35	5	10	52	431	10	5	2	16	0
	Flex	.00	.00	.00	.34	.26	.23	.36	.37	.67	.50	.25	.43	.79	0.00
	Rigid	.00	.00	.00	.47	.26	.29	.37	.37	1.16	1.02	.25	.44	1.21	0.00
	GVW	2.1	4.1	5.1	31.3	17.4	24.4	22.9	23.0	58.3	70.6	31.1	47.5	64.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2019

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9