

Idaho Transportation Department

Monthly WIM Distribution for Nov-2019

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	1,688	1,121	11	45	7	13	52	722	21	8	3	31	0
	Flex	.00	.00	.00	.37	.25	.26	.25	.23	.57	.44	.39	.31	.67	0.00
	Rigid	.00	.00	.00	.53	.24	.34	.27	.24	.99	.86	.38	.32	1.00	0.00
	GVW	3.9	4.0	4.9	33.2	16.7	25.5	22.8	22.4	55.4	64.3	34.7	44.9	64.0	0.0
N	Num	1	816	511	5	20	4	5	18	305	14	3	2	15	0
	Flex	.00	.00	.00	.37	.23	.22	.20	.14	.47	.43	.45	.35	.69	0.00
	Rigid	.00	.00	.00	.53	.22	.28	.21	.17	.78	.84	.44	.39	1.05	0.00
	GVW	5.3	4.0	4.7	32.2	16.4	23.9	23.7	22.2	51.8	65.1	40.6	47.6	66.1	0.0
S	Num	1	872	610	6	26	4	8	34	417	8	5	2	15	0
	Flex	.00	.00	.00	.35	.27	.30	.28	.26	.64	.46	.34	.30	.66	0.00
	Rigid	.00	.00	.00	.50	.26	.41	.30	.27	1.13	.93	.34	.32	.94	0.00
	GVW	2.4	4.0	5.1	33.3	17.0	27.0	22.3	22.2	57.9	64.3	32.0	45.5	62.0	0.0
N Lane1	Num	1	816	511	5	20	4	5	18	305	14	3	2	15	0
	Flex	.00	.00	.00	.37	.23	.22	.20	.14	.47	.43	.45	.35	.69	0.00
	Rigid	.00	.00	.00	.53	.22	.28	.21	.17	.78	.84	.44	.39	1.05	0.00
	GVW	5.3	4.0	4.7	32.2	16.4	23.9	23.7	22.2	51.8	65.1	40.6	47.6	66.1	0.0
S Lane1	Num	1	872	610	6	26	4	8	34	417	8	5	2	15	0
	Flex	.00	.00	.00	.35	.27	.30	.28	.26	.64	.46	.34	.30	.66	0.00
	Rigid	.00	.00	.00	.50	.26	.41	.30	.27	1.13	.93	.34	.32	.94	0.00
	GVW	2.4	4.0	5.1	33.3	17.0	27.0	22.3	22.2	57.9	64.3	32.0	45.5	62.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2019

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9