

# Idaho Transportation Department

## Monthly WIM Distribution for Dec-2019

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	1,547	975	15	34	9	7	31	643	15	8	4	18	0
	Flex	.00	.00	.00	.29	.21	.25	.18	.19	.57	.41	.46	.60	.73	0.00
	Rigid	.00	.00	.00	.44	.20	.35	.19	.20	.98	.83	.45	.67	1.05	0.00
	GVW	3.3	4.1	4.8	32.6	16.4	24.7	21.9	22.4	55.4	66.9	39.7	52.7	67.9	0.0
N	Num	1	761	452	7	14	4	3	13	280	8	4	2	9	0
	Flex	.00	.00	.00	.31	.18	.24	.15	.17	.46	.38	.55	.40	.71	0.00
	Rigid	.00	.00	.00	.46	.18	.34	.16	.18	.75	.73	.53	.42	1.07	0.00
	GVW	4.0	4.1	4.6	33.0	16.0	24.0	22.6	23.2	51.4	64.0	44.8	52.2	69.5	0.0
S	Num	1	785	523	8	20	5	5	19	363	8	5	2	9	0
	Flex	.00	.00	.00	.27	.22	.27	.18	.21	.65	.44	.40	.66	.76	0.00
	Rigid	.00	.00	.00	.41	.22	.37	.19	.21	1.15	.88	.40	.76	1.06	0.00
	GVW	2.6	4.0	5.0	32.1	16.6	25.5	21.4	21.8	58.5	68.0	36.0	51.7	67.0	0.0
N Lane1	Num	1	761	452	7	14	4	3	13	280	8	4	2	9	0
	Flex	.00	.00	.00	.31	.18	.24	.15	.17	.46	.38	.55	.40	.71	0.00
	Rigid	.00	.00	.00	.46	.18	.34	.16	.18	.75	.73	.53	.42	1.07	0.00
	GVW	4.0	4.1	4.6	33.0	16.0	24.0	22.6	23.2	51.4	64.0	44.8	52.2	69.5	0.0
S Lane1	Num	1	785	523	8	20	5	5	19	363	8	5	2	9	0
	Flex	.00	.00	.00	.27	.22	.27	.18	.21	.65	.44	.40	.66	.76	0.00
	Rigid	.00	.00	.00	.41	.22	.37	.19	.21	1.15	.88	.40	.76	1.06	0.00
	GVW	2.6	4.0	5.0	32.1	16.6	25.5	21.4	21.8	58.5	68.0	36.0	51.7	67.0	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Dec-2019

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9