

Idaho Transportation Department

Monthly WIM Distribution for Jan-2020

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	1,337	854	13	33	10	7	36	728	19	8	3	18	0
	Flex	.00	.00	.00	.33	.25	.32	.25	.19	.60	.47	.49	.66	.69	0.00
	Rigid	.00	.00	.00	.49	.25	.46	.26	.20	1.02	.96	.50	.73	1.07	0.00
	GVW	2.1	4.1	4.8	32.2	17.3	27.1	22.3	23.9	56.0	69.8	40.8	53.7	69.0	0.0
N	Num	1	679	408	7	14	5	2	18	323	9	4	2	9	0
	Flex	.00	.00	.00	.38	.22	.34	.23	.18	.49	.40	.53	.33	.62	0.00
	Rigid	.00	.00	.00	.56	.21	.49	.23	.19	.80	.85	.50	.35	.98	0.00
	GVW	1.9	4.1	4.6	33.0	17.1	27.8	23.0	24.7	51.6	69.5	42.2	50.9	70.1	0.0
S	Num	1	659	446	7	20	5	5	18	404	10	5	2	9	0
	Flex	.00	.00	.00	.28	.29	.31	.25	.21	.69	.54	.45	1.01	.76	0.00
	Rigid	.00	.00	.00	.42	.28	.46	.25	.22	1.20	1.08	.46	1.14	1.18	0.00
	GVW	2.0	4.1	5.0	31.4	17.5	27.2	21.8	23.1	59.5	69.9	38.7	55.5	68.8	0.0
N Lane1	Num	1	679	408	7	14	5	2	18	323	9	4	2	9	0
	Flex	.00	.00	.00	.38	.22	.34	.23	.18	.49	.40	.53	.33	.62	0.00
	Rigid	.00	.00	.00	.56	.21	.49	.23	.19	.80	.85	.50	.35	.98	0.00
	GVW	1.9	4.1	4.6	33.0	17.1	27.8	23.0	24.7	51.6	69.5	42.2	50.9	70.1	0.0
S Lane1	Num	1	659	446	7	20	5	5	18	404	10	5	2	9	0
	Flex	.00	.00	.00	.28	.29	.31	.25	.21	.69	.54	.45	1.01	.76	0.00
	Rigid	.00	.00	.00	.42	.28	.46	.25	.22	1.20	1.08	.46	1.14	1.18	0.00
	GVW	2.0	4.1	5.0	31.4	17.5	27.2	21.8	23.1	59.5	69.9	38.7	55.5	68.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2020

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9