

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2020

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	665	558	2	31	8	8	44	686	20	6	2	23	0
	Flex	.00	.00	.00	.47	.33	.25	.44	.28	.67	.47	.49	.35	.78	0.00
	Rigid	.00	.00	.00	.59	.33	.35	.45	.29	1.15	.96	.48	.37	1.10	0.00
	GVW	2.8	4.0	5.0	27.3	17.9	24.2	25.0	21.9	57.0	67.5	37.4	47.1	65.3	0.0
N	Num	1	362	307	2	15	4	5	31	319	8	4	2	12	0
	Flex	.00	.00	.00	.46	.30	.29	.62	.36	.65	.44	.55	.34	.81	0.00
	Rigid	.00	.00	.00	.63	.30	.38	.64	.37	1.07	.89	.54	.36	1.22	0.00
	GVW	2.7	4.0	5.0	29.0	18.2	24.9	27.7	23.0	55.6	62.9	37.6	45.8	66.1	0.0
S	Num	1	304	251	2	16	4	3	13	367	12	2	1	11	0
	Flex	.00	.00	.00	.46	.36	.24	.18	.08	.68	.50	.48	.47	.79	0.00
	Rigid	.00	.00	.00	.58	.35	.35	.18	.08	1.21	1.04	.47	.48	1.14	0.00
	GVW	3.2	3.9	4.9	29.0	17.6	24.5	20.4	19.2	58.1	71.0	39.0	51.2	68.8	0.0
N Lane1	Num	1	362	307	2	15	4	5	31	319	8	4	2	12	0
	Flex	.00	.00	.00	.46	.30	.29	.62	.36	.65	.44	.55	.34	.81	0.00
	Rigid	.00	.00	.00	.63	.30	.38	.64	.37	1.07	.89	.54	.36	1.22	0.00
	GVW	2.7	4.0	5.0	29.0	18.2	24.9	27.7	23.0	55.6	62.9	37.6	45.8	66.1	0.0
S Lane1	Num	1	304	251	2	16	4	3	13	367	12	2	1	11	0
	Flex	.00	.00	.00	.46	.36	.24	.18	.08	.68	.50	.48	.47	.79	0.00
	Rigid	.00	.00	.00	.58	.35	.35	.18	.08	1.21	1.04	.47	.48	1.14	0.00
	GVW	3.2	3.9	4.9	29.0	17.6	24.5	20.4	19.2	58.1	71.0	39.0	51.2	68.8	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2020

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9