

Idaho Transportation Department

Monthly WIM Distribution for May-2020

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	1,095	836	2	43	9	10	51	748	19	7	2	23	0
	Flex	.00	.00	.00	.60	.27	.25	.34	.26	.68	.53	.59	.41	.79	0.00
	Rigid	.00	.00	.00	.73	.27	.35	.35	.27	1.18	1.06	.58	.42	1.08	0.00
	GVW	1.3	4.0	5.0	31.4	16.8	24.4	23.4	21.2	57.2	66.1	38.4	46.1	63.8	0.0
N	Num	1	596	442	1	20	5	6	32	349	8	4	2	12	0
	Flex	.00	.00	.00	.58	.24	.26	.41	.34	.69	.54	.73	.33	.63	0.00
	Rigid	.00	.00	.00	.73	.24	.36	.42	.35	1.18	1.05	.71	.35	.74	0.00
	GVW	1.3	4.1	5.0	30.5	17.0	24.4	24.8	22.2	57.2	64.9	40.9	44.4	54.7	0.0
S	Num	1	498	394	2	22	4	5	19	399	11	3	2	11	0
	Flex	.00	.00	.00	.38	.29	.21	.23	.13	.67	.54	.42	.37	1.07	0.00
	Rigid	.00	.00	.00	.45	.29	.28	.24	.14	1.18	1.08	.40	.38	1.60	0.00
	GVW	1.3	4.0	5.0	28.5	16.7	23.6	21.4	19.3	57.2	67.0	36.9	45.0	77.3	0.0
N Lane1	Num	1	596	442	1	20	5	6	32	349	8	4	2	12	0
	Flex	.00	.00	.00	.58	.24	.26	.41	.34	.69	.54	.73	.33	.63	0.00
	Rigid	.00	.00	.00	.73	.24	.36	.42	.35	1.18	1.05	.71	.35	.74	0.00
	GVW	1.3	4.1	5.0	30.5	17.0	24.4	24.8	22.2	57.2	64.9	40.9	44.4	54.7	0.0
S Lane1	Num	1	498	394	2	22	4	5	19	399	11	3	2	11	0
	Flex	.00	.00	.00	.38	.29	.21	.23	.13	.67	.54	.42	.37	1.07	0.00
	Rigid	.00	.00	.00	.45	.29	.28	.24	.14	1.18	1.08	.40	.38	1.60	0.00
	GVW	1.3	4.0	5.0	28.5	16.7	23.6	21.4	19.3	57.2	67.0	36.9	45.0	77.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2020

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9