

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2020

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	2,016	1,237	3	61	9	13	66	771	18	5	3	26	0
	Flex	.00	.00	.00	.56	.24	.21	.43	.23	.68	.57	.53	.55	.97	0.00
	Rigid	.00	.00	.00	.66	.23	.27	.45	.25	1.18	1.17	.52	.63	1.35	0.00
	GVW	1.4	4.0	5.0	27.2	16.3	23.8	23.2	20.3	57.3	70.2	37.3	53.8	68.8	0.0
N	Num	1	1,075	636	1	30	5	6	38	363	8	3	2	13	0
	Flex	.00	.00	.00	.70	.27	.21	.65	.27	.70	.54	.79	.33	1.11	0.00
	Rigid	.00	.00	.00	.81	.27	.28	.70	.29	1.20	1.12	.76	.34	1.45	0.00
	GVW	.9	4.1	5.0	27.2	17.2	23.7	25.1	20.8	57.7	65.1	43.4	45.6	69.5	0.0
S	Num	1	941	601	2	30	4	7	28	408	10	3	2	13	0
	Flex	.00	.00	.00	.56	.20	.20	.26	.17	.66	.57	.40	.61	.80	0.00
	Rigid	.00	.00	.00	.66	.20	.26	.27	.18	1.16	1.16	.39	.73	1.18	0.00
	GVW	1.8	3.9	5.0	29.7	15.4	23.5	21.5	19.6	56.9	72.9	35.1	58.2	66.7	0.0
N Lane1	Num	1	1,075	636	1	30	5	6	38	363	8	3	2	13	0
	Flex	.00	.00	.00	.70	.27	.21	.65	.27	.70	.54	.79	.33	1.11	0.00
	Rigid	.00	.00	.00	.81	.27	.28	.70	.29	1.20	1.12	.76	.34	1.45	0.00
	GVW	.9	4.1	5.0	27.2	17.2	23.7	25.1	20.8	57.7	65.1	43.4	45.6	69.5	0.0
S Lane1	Num	1	941	601	2	30	4	7	28	408	10	3	2	13	0
	Flex	.00	.00	.00	.56	.20	.20	.26	.17	.66	.57	.40	.61	.80	0.00
	Rigid	.00	.00	.00	.66	.20	.26	.27	.18	1.16	1.16	.39	.73	1.18	0.00
	GVW	1.8	3.9	5.0	29.7	15.4	23.5	21.5	19.6	56.9	72.9	35.1	58.2	66.7	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2020

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9