

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2020

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2,779	2,348	1,432	3	78	10	14	75	717	18	6	4	20	0
	Flex	.10	.00	.00	.50	.25	.29	.34	.25	.74	.56	.54	.31	.93	0.00
	Rigid	.16	.00	.00	.59	.24	.40	.35	.26	1.29	1.23	.53	.34	1.27	0.00
	GVW	10.1	4.0	4.9	28.1	16.3	25.0	22.8	19.7	57.8	69.5	35.6	43.8	65.0	0.0
N	Num	1,915	1,218	707	2	36	5	6	39	337	7	3	2	9	0
	Flex	.13	.00	.00	.71	.29	.30	.42	.30	.78	.68	.73	.36	1.04	0.00
	Rigid	.22	.00	.00	.79	.29	.44	.42	.31	1.35	1.50	.72	.38	1.35	0.00
	GVW	12.4	4.1	4.9	29.4	17.0	26.2	23.7	20.4	58.2	65.9	41.1	49.2	63.5	0.0
S	Num	1,425	1,129	725	2	42	5	8	37	380	11	3	2	11	0
	Flex	.09	.00	.00	.44	.21	.25	.30	.21	.70	.47	.35	.24	.84	0.00
	Rigid	.16	.00	.00	.52	.21	.33	.31	.22	1.23	1.04	.35	.31	1.23	0.00
	GVW	10.6	4.0	5.0	27.8	15.7	23.6	22.2	18.9	57.4	70.4	31.7	39.8	66.5	0.0
N Lane1	Num	1,915	1,218	707	2	36	5	6	39	337	7	3	2	9	0
	Flex	.13	.00	.00	.71	.29	.30	.42	.30	.78	.68	.73	.36	1.04	0.00
	Rigid	.22	.00	.00	.79	.29	.44	.42	.31	1.35	1.50	.72	.38	1.35	0.00
	GVW	12.4	4.1	4.9	29.4	17.0	26.2	23.7	20.4	58.2	65.9	41.1	49.2	63.5	0.0
S Lane1	Num	1,425	1,129	725	2	42	5	8	37	380	11	3	2	11	0
	Flex	.09	.00	.00	.44	.21	.25	.30	.21	.70	.47	.35	.24	.84	0.00
	Rigid	.16	.00	.00	.52	.21	.33	.31	.22	1.23	1.04	.35	.31	1.23	0.00
	GVW	10.6	4.0	5.0	27.8	15.7	23.6	22.2	18.9	57.4	70.4	31.7	39.8	66.5	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2020

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9