

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2021

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	4,320	0	0	0	0	0	0	0	0	0	0	0	0	0
	Flex	.22	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	Rigid	.40	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	GVW	16.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
N	Num	2,237	0	0	0	0	0	0	0	0	0	0	0	0	0
	Flex	.20	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	Rigid	.34	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	GVW	15.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
S	Num	2,083	0	0	0	0	0	0	0	0	0	0	0	0	0
	Flex	.25	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	Rigid	.47	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	GVW	17.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
N Lane1	Num	2,237	0	0	0	0	0	0	0	0	0	0	0	0	0
	Flex	.20	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	Rigid	.34	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	GVW	15.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
S Lane1	Num	2,083	0	0	0	0	0	0	0	0	0	0	0	0	0
	Flex	.25	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	Rigid	.47	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	GVW	17.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2021

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 0.5 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 5

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9