

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2022

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	23	2,612	1,285	18	131	190	5	98	668	24	12	11	13	0
	Flex	.01	.00	.00	.54	.24	.31	.27	.12	.75	.53	1.86	.74	1.18	0.00
	Rigid	.03	.00	.00	.74	.24	.53	.63	.14	1.34	1.17	1.96	1.09	2.02	0.00
	GVW	11.8	2.6	4.6	37.3	17.4	32.6	45.1	21.3	59.7	70.6	63.2	61.2	86.5	0.0
N	Num	7	1,318	642	7	56	69	1	45	329	9	7	5	7	0
	Flex	.02	.00	.00	.65	.36	.41	.22	.15	1.03	.77	2.37	.83	1.39	0.00
	Rigid	.04	.00	.00	.92	.35	.74	.61	.18	1.90	1.78	2.47	1.06	2.55	0.00
	GVW	12.6	2.6	4.7	39.3	18.9	34.1	42.1	21.7	64.8	75.2	69.4	57.5	86.6	0.0
S	Num	17	1,295	643	10	75	122	5	53	338	15	6	6	6	0
	Flex	.01	.00	.00	.43	.16	.25	.28	.09	.47	.36	1.21	.67	1.03	0.00
	Rigid	.03	.00	.00	.56	.16	.42	.65	.10	.79	.75	1.18	1.12	1.47	0.00
	GVW	11.4	2.6	4.5	35.7	16.3	31.7	45.8	20.9	54.6	67.3	56.0	63.4	85.9	0.0
N Lane1	Num	7	1,318	642	7	56	69	1	45	329	9	7	5	7	0
	Flex	.02	.00	.00	.65	.36	.41	.22	.15	1.03	.77	2.37	.83	1.39	0.00
	Rigid	.04	.00	.00	.92	.35	.74	.61	.18	1.90	1.78	2.47	1.06	2.55	0.00
	GVW	12.6	2.6	4.7	39.3	18.9	34.1	42.1	21.7	64.8	75.2	69.4	57.5	86.6	0.0
S Lane1	Num	17	1,295	643	10	75	122	5	53	338	15	6	6	6	0
	Flex	.01	.00	.00	.43	.16	.25	.28	.09	.47	.36	1.21	.67	1.03	0.00
	Rigid	.03	.00	.00	.56	.16	.42	.65	.10	.79	.75	1.18	1.12	1.47	0.00
	GVW	11.4	2.6	4.5	35.7	16.3	31.7	45.8	20.9	54.6	67.3	56.0	63.4	85.9	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2022

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9