

Idaho Transportation Department

Monthly WIM Distribution for Oct-2022

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	23	2,300	1,233	22	132	167	3	103	691	20	17	9	14	0
	Flex	.04	.00	.00	.62	.33	.36	.44	.15	.80	.60	1.43	.94	1.28	0.00
	Rigid	.08	.00	.00	.82	.33	.64	.98	.17	1.45	1.35	1.40	1.35	2.08	0.00
	GVW	13.1	2.6	4.7	38.5	18.8	34.1	51.2	23.9	61.3	72.1	59.1	64.5	85.5	0.0
N	Num	8	1,061	557	7	43	71	1	36	310	10	9	4	7	0
	Flex	.05	.00	.00	.74	.32	.43	.43	.19	.99	.71	1.72	1.16	1.24	0.00
	Rigid	.11	.00	.00	1.06	.32	.78	.95	.24	1.83	1.66	1.67	1.47	2.20	0.00
	GVW	13.8	2.6	4.6	40.0	18.3	34.9	51.2	25.2	64.0	75.1	64.6	64.6	83.4	0.0
S	Num	15	1,239	676	15	90	96	2	67	381	10	9	6	6	0
	Flex	.03	.00	.01	.57	.33	.32	.41	.12	.65	.47	1.15	.69	1.13	0.00
	Rigid	.06	.00	.01	.71	.33	.54	.86	.14	1.14	1.01	1.14	1.12	1.58	0.00
	GVW	12.7	2.6	4.8	37.8	19.0	33.5	48.0	23.2	59.2	69.1	54.4	61.6	82.7	0.0
N Lane1	Num	8	1,061	557	7	43	71	1	36	310	10	9	4	7	0
	Flex	.05	.00	.00	.74	.32	.43	.43	.19	.99	.71	1.72	1.16	1.24	0.00
	Rigid	.11	.00	.00	1.06	.32	.78	.95	.24	1.83	1.66	1.67	1.47	2.20	0.00
	GVW	13.8	2.6	4.6	40.0	18.3	34.9	51.2	25.2	64.0	75.1	64.6	64.6	83.4	0.0
S Lane1	Num	15	1,239	676	15	90	96	2	67	381	10	9	6	6	0
	Flex	.03	.00	.01	.57	.33	.32	.41	.12	.65	.47	1.15	.69	1.13	0.00
	Rigid	.06	.00	.01	.71	.33	.54	.86	.14	1.14	1.01	1.14	1.12	1.58	0.00
	GVW	12.7	2.6	4.8	37.8	19.0	33.5	48.0	23.2	59.2	69.1	54.4	61.6	82.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2022

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9