

Idaho Transportation Department

Monthly WIM Distribution for Dec-2022

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	22	1,600	832	11	62	137	4	48	524	23	19	8	7	0
	Flex	.04	.00	.00	.62	.19	.40	.28	.15	.95	.55	1.36	1.06	1.33	0.00
	Rigid	.08	.00	.00	.88	.18	.72	.61	.18	1.75	1.33	1.31	1.51	2.13	0.00
	GVW	13.7	2.5	4.2	39.2	16.4	34.6	43.4	25.0	64.8	76.6	58.8	68.7	87.9	0.0
N	Num	8	785	400	5	30	57	3	22	233	14	9	3	4	0
	Flex	.05	.00	.00	.62	.17	.38	.21	.17	.86	.50	1.54	1.02	.91	0.00
	Rigid	.12	.01	.00	.89	.17	.68	.49	.20	1.57	1.21	1.48	1.23	1.63	0.00
	GVW	13.5	2.6	4.2	39.5	16.2	34.1	38.9	25.9	62.5	72.2	61.5	65.4	76.9	0.0
S	Num	14	814	432	6	33	80	2	26	292	9	10	5	4	0
	Flex	.03	.00	.00	.56	.20	.41	.37	.14	1.01	.58	1.17	1.07	1.69	0.00
	Rigid	.05	.00	.00	.78	.19	.75	.86	.16	1.88	1.38	1.13	1.69	2.58	0.00
	GVW	13.7	2.4	4.2	37.6	16.6	35.0	50.7	24.3	66.5	76.8	56.1	70.6	91.5	0.0
N Lane1	Num	8	785	400	5	30	57	3	22	233	14	9	3	4	0
	Flex	.05	.00	.00	.62	.17	.38	.21	.17	.86	.50	1.54	1.02	.91	0.00
	Rigid	.12	.01	.00	.89	.17	.68	.49	.20	1.57	1.21	1.48	1.23	1.63	0.00
	GVW	13.5	2.6	4.2	39.5	16.2	34.1	38.9	25.9	62.5	72.2	61.5	65.4	76.9	0.0
S Lane1	Num	14	814	432	6	33	80	2	26	292	9	10	5	4	0
	Flex	.03	.00	.00	.56	.20	.41	.37	.14	1.01	.58	1.17	1.07	1.69	0.00
	Rigid	.05	.00	.00	.78	.19	.75	.86	.16	1.88	1.38	1.13	1.69	2.58	0.00
	GVW	13.7	2.4	4.2	37.6	16.6	35.0	50.7	24.3	66.5	76.8	56.1	70.6	91.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2022

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9