

Idaho Transportation Department

Monthly WIM Distribution for Jan-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	25	1,596	815	12	65	153	4	54	586	23	19	8	13	0
	Flex	.03	.00	.00	.61	.23	.40	.38	.18	1.00	.61	1.74	1.17	1.49	0.00
	Rigid	.07	.00	.00	.89	.22	.73	.87	.21	1.81	1.43	1.71	1.74	2.49	0.00
	GVW	13.4	2.5	4.3	40.1	17.2	34.8	49.3	26.1	65.1	75.8	62.4	71.8	90.7	0.0
N	Num	9	796	399	6	30	64	3	25	265	10	10	4	7	0
	Flex	.04	.01	.00	.66	.22	.39	.37	.19	.92	.62	2.38	1.30	1.34	0.00
	Rigid	.09	.01	.00	.98	.21	.70	.88	.22	1.70	1.45	2.37	1.65	2.43	0.00
	GVW	12.9	2.6	4.3	41.3	17.0	34.1	46.0	27.7	63.3	75.5	68.5	69.4	88.1	0.0
S	Num	16	801	416	6	35	88	3	29	321	13	9	4	6	0
	Flex	.03	.00	.00	.55	.23	.41	.37	.17	1.05	.59	1.05	1.00	1.66	0.00
	Rigid	.06	.00	.00	.79	.23	.75	.83	.20	1.89	1.36	1.00	1.63	2.54	0.00
	GVW	13.8	2.4	4.2	39.1	17.4	35.2	51.0	24.6	66.5	75.4	55.3	70.0	93.7	0.0
N Lane1	Num	9	796	399	6	30	64	3	25	265	10	10	4	7	0
	Flex	.04	.01	.00	.66	.22	.39	.37	.19	.92	.62	2.38	1.30	1.34	0.00
	Rigid	.09	.01	.00	.98	.21	.70	.88	.22	1.70	1.45	2.37	1.65	2.43	0.00
	GVW	12.9	2.6	4.3	41.3	17.0	34.1	46.0	27.7	63.3	75.5	68.5	69.4	88.1	0.0
S Lane1	Num	16	801	416	6	35	88	3	29	321	13	9	4	6	0
	Flex	.03	.00	.00	.55	.23	.41	.37	.17	1.05	.59	1.05	1.00	1.66	0.00
	Rigid	.06	.00	.00	.79	.23	.75	.83	.20	1.89	1.36	1.00	1.63	2.54	0.00
	GVW	13.8	2.4	4.2	39.1	17.4	35.2	51.0	24.6	66.5	75.4	55.3	70.0	93.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9