

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2023

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	23	1,749	876	12	78	145	5	56	569	34	16	11	19	0
	Flex	.04	.01	.00	.66	.21	.37	.22	.17	.91	.56	1.67	.89	1.09	0.00
	Rigid	.08	.01	.00	.96	.20	.67	.49	.20	1.67	1.32	1.67	1.36	1.75	0.00
	GVW	13.0	2.6	4.2	39.7	16.9	34.2	41.0	25.5	64.1	73.0	60.2	65.4	83.5	0.0
N	Num	8	872	433	7	39	60	1	29	268	15	9	4	9	0
	Flex	.06	.01	.00	.72	.23	.40	.36	.16	.98	.71	2.37	1.05	1.25	0.00
	Rigid	.14	.01	.00	1.09	.22	.74	.88	.19	1.83	1.66	2.42	1.46	2.08	0.00
	GVW	13.6	2.7	4.4	42.4	17.3	34.5	42.0	25.8	64.9	75.5	66.4	65.6	86.5	0.0
S	Num	15	877	443	5	39	86	4	27	301	19	8	7	9	0
	Flex	.02	.00	.00	.60	.18	.35	.21	.18	.84	.46	1.00	.78	1.04	0.00
	Rigid	.04	.00	.00	.81	.18	.62	.42	.22	1.53	1.09	.97	1.30	1.57	0.00
	GVW	12.7	2.4	4.1	36.3	16.5	33.9	41.4	25.2	63.4	71.8	53.8	65.7	81.6	0.0
N Lane1	Num	8	872	433	7	39	60	1	29	268	15	9	4	9	0
	Flex	.06	.01	.00	.72	.23	.40	.36	.16	.98	.71	2.37	1.05	1.25	0.00
	Rigid	.14	.01	.00	1.09	.22	.74	.88	.19	1.83	1.66	2.42	1.46	2.08	0.00
	GVW	13.6	2.7	4.4	42.4	17.3	34.5	42.0	25.8	64.9	75.5	66.4	65.6	86.5	0.0
S Lane1	Num	15	877	443	5	39	86	4	27	301	19	8	7	9	0
	Flex	.02	.00	.00	.60	.18	.35	.21	.18	.84	.46	1.00	.78	1.04	0.00
	Rigid	.04	.00	.00	.81	.18	.62	.42	.22	1.53	1.09	.97	1.30	1.57	0.00
	GVW	12.7	2.4	4.1	36.3	16.5	33.9	41.4	25.2	63.4	71.8	53.8	65.7	81.6	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2023

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9