

Idaho Transportation Department

Monthly WIM Distribution for Mar-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	26	1,974	1,018	19	108	154	4	72	579	35	19	12	17	0
	Flex	.05	.00	.00	.60	.25	.33	.36	.15	.84	.43	2.01	.71	1.36	0.00
	Rigid	.11	.00	.01	.81	.25	.58	.88	.18	1.54	1.02	2.04	1.07	2.46	0.00
	GVW	13.0	2.6	4.4	37.1	17.6	33.0	45.5	25.4	62.7	67.9	62.2	62.1	87.5	0.0
N	Num	9	1,009	529	11	62	63	2	43	283	13	10	5	9	0
	Flex	.08	.01	.01	.71	.32	.40	.73	.15	1.00	.64	2.89	.84	1.88	0.00
	Rigid	.17	.01	.01	.99	.32	.73	1.80	.18	1.84	1.49	2.96	1.14	3.68	0.00
	GVW	13.5	2.7	4.7	39.4	18.9	34.0	51.6	25.8	64.9	74.0	68.2	60.6	96.2	0.0
S	Num	17	966	488	9	46	91	4	29	296	22	9	7	9	0
	Flex	.02	.00	.00	.46	.16	.28	.19	.15	.69	.32	1.08	.59	.85	0.00
	Rigid	.05	.00	.00	.59	.15	.48	.43	.18	1.25	.76	1.05	.98	1.32	0.00
	GVW	12.6	2.4	4.0	33.9	15.7	32.3	41.7	24.7	60.5	64.8	55.5	62.1	79.0	0.0
N Lane1	Num	9	1,009	529	11	62	63	2	43	283	13	10	5	9	0
	Flex	.08	.01	.01	.71	.32	.40	.73	.15	1.00	.64	2.89	.84	1.88	0.00
	Rigid	.17	.01	.01	.99	.32	.73	1.80	.18	1.84	1.49	2.96	1.14	3.68	0.00
	GVW	13.5	2.7	4.7	39.4	18.9	34.0	51.6	25.8	64.9	74.0	68.2	60.6	96.2	0.0
S Lane1	Num	17	966	488	9	46	91	4	29	296	22	9	7	9	0
	Flex	.02	.00	.00	.46	.16	.28	.19	.15	.69	.32	1.08	.59	.85	0.00
	Rigid	.05	.00	.00	.59	.15	.48	.43	.18	1.25	.76	1.05	.98	1.32	0.00
	GVW	12.6	2.4	4.0	33.9	15.7	32.3	41.7	24.7	60.5	64.8	55.5	62.1	79.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9