

Idaho Transportation Department

Monthly WIM Distribution for Jun-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	23	2,547	1,352	21	143	163	5	108	739	30	18	14	12	0
	Flex	.02	.00	.00	.43	.17	.23	.34	.09	.51	.37	1.27	.54	.93	0.00
	Rigid	.03	.00	.00	.56	.16	.38	.61	.10	.86	.80	1.24	.82	1.39	0.00
	GVW	11.4	2.7	4.7	34.8	17.2	30.3	45.4	21.3	55.3	67.1	55.3	58.8	81.4	0.0
N	Num	8	1,340	706	10	73	72	1	55	369	13	9	7	6	0
	Flex	.02	.00	.00	.50	.18	.23	.27	.09	.56	.39	1.43	.56	.88	0.00
	Rigid	.04	.00	.00	.67	.18	.37	.51	.10	.94	.79	1.40	.76	1.33	0.00
	GVW	11.4	2.7	4.8	36.3	17.9	29.7	42.8	21.3	56.0	62.7	56.8	58.0	76.1	0.0
S	Num	15	1,207	646	10	70	91	4	54	370	17	9	7	6	0
	Flex	.01	.00	.00	.37	.15	.23	.34	.09	.47	.37	1.08	.51	.94	0.00
	Rigid	.03	.00	.00	.46	.15	.38	.63	.11	.79	.81	1.06	.84	1.35	0.00
	GVW	11.5	2.7	4.6	33.6	16.5	30.8	45.6	21.3	54.7	70.5	53.6	58.8	84.7	0.0
N Lane1	Num	8	1,340	706	10	73	72	1	55	369	13	9	7	6	0
	Flex	.02	.00	.00	.50	.18	.23	.27	.09	.56	.39	1.43	.56	.88	0.00
	Rigid	.04	.00	.00	.67	.18	.37	.51	.10	.94	.79	1.40	.76	1.33	0.00
	GVW	11.4	2.7	4.8	36.3	17.9	29.7	42.8	21.3	56.0	62.7	56.8	58.0	76.1	0.0
S Lane1	Num	15	1,207	646	10	70	91	4	54	370	17	9	7	6	0
	Flex	.01	.00	.00	.37	.15	.23	.34	.09	.47	.37	1.08	.51	.94	0.00
	Rigid	.03	.00	.00	.46	.15	.38	.63	.11	.79	.81	1.06	.84	1.35	0.00
	GVW	11.5	2.7	4.6	33.6	16.5	30.8	45.6	21.3	54.7	70.5	53.6	58.8	84.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9