

Idaho Transportation Department

Monthly WIM Distribution for Aug-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	16	2,411	1,180	19	112	547	5	88	192	16	1	4	5	0
	Flex	.04	.00	.00	.83	.33	.54	.39	.11	1.07	.75	1.45	.61	1.49	0.00
	Rigid	.08	.00	.00	1.15	.34	1.03	.98	.13	1.88	1.70	1.66	.85	2.82	0.00
	GVW	13.3	2.6	4.3	36.2	17.6	36.4	49.5	20.8	61.0	72.8	52.5	57.1	96.1	0.0
N	Num	5	1,201	567	7	42	252	2	36	75	7	1	2	3	0
	Flex	.02	.00	.00	.84	.37	.45	.36	.10	1.00	.69	.98	.56	1.77	0.00
	Rigid	.04	.00	.00	1.20	.38	.85	1.01	.12	1.69	1.61	1.44	.75	3.51	0.00
	GVW	11.2	2.4	4.2	37.1	17.7	34.5	48.8	19.7	58.7	71.5	43.1	54.6	102.2	0.0
S	Num	11	1,210	613	12	70	296	4	52	117	9	1	3	4	0
	Flex	.05	.00	.00	.85	.31	.61	.41	.12	1.11	.81	2.09	.57	1.16	0.00
	Rigid	.10	.01	.00	1.15	.32	1.19	1.03	.13	1.99	1.79	2.08	.84	2.00	0.00
	GVW	14.2	2.7	4.4	36.0	17.5	38.1	52.7	21.6	62.5	73.9	60.4	58.0	88.5	0.0
N Lane1	Num	5	1,201	567	7	42	252	2	36	75	7	1	2	3	0
	Flex	.02	.00	.00	.84	.37	.45	.36	.10	1.00	.69	.98	.56	1.77	0.00
	Rigid	.04	.00	.00	1.20	.38	.85	1.01	.12	1.69	1.61	1.44	.75	3.51	0.00
	GVW	11.2	2.4	4.2	37.1	17.7	34.5	48.8	19.7	58.7	71.5	43.1	54.6	102.2	0.0
S Lane1	Num	11	1,210	613	12	70	296	4	52	117	9	1	3	4	0
	Flex	.05	.00	.00	.85	.31	.61	.41	.12	1.11	.81	2.09	.57	1.16	0.00
	Rigid	.10	.01	.00	1.15	.32	1.19	1.03	.13	1.99	1.79	2.08	.84	2.00	0.00
	GVW	14.2	2.7	4.4	36.0	17.5	38.1	52.7	21.6	62.5	73.9	60.4	58.0	88.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Aug-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9