

Idaho Transportation Department

Monthly WIM Distribution for Sep-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	13	2,285	1,166	18	118	561	4	91	186	15	1	5	5	0
	Flex	.04	.00	.00	.69	.31	.50	.35	.09	1.06	.75	1.59	.77	1.42	0.00
	Rigid	.09	.00	.00	.93	.31	.96	.94	.11	1.84	1.74	1.64	1.08	2.69	0.00
	GVW	14.1	2.5	4.4	36.4	17.6	36.6	50.9	20.7	61.9	73.1	58.9	62.3	96.2	0.0
N	Num	4	1,112	543	7	45	255	2	36	70	7	1	2	2	0
	Flex	.03	.00	.00	.66	.30	.42	.36	.09	.94	.67	1.22	.86	2.51	0.00
	Rigid	.07	.00	.00	.91	.30	.78	1.00	.10	1.55	1.54	1.35	1.19	4.70	0.00
	GVW	12.0	2.4	4.3	36.4	17.1	34.7	51.2	19.8	58.5	72.9	47.8	63.5	114.6	0.0
S	Num	9	1,172	623	11	73	307	3	55	116	9	2	3	3	0
	Flex	.04	.00	.00	.71	.31	.57	.34	.10	1.13	.80	1.52	.67	.79	0.00
	Rigid	.09	.00	.00	.94	.31	1.10	.88	.12	2.01	1.84	1.47	.97	1.56	0.00
	GVW	15.0	2.6	4.4	36.2	17.8	38.1	49.8	21.3	63.9	72.3	60.1	61.0	85.1	0.0
N Lane1	Num	4	1,112	543	7	45	255	2	36	70	7	1	2	2	0
	Flex	.03	.00	.00	.66	.30	.42	.36	.09	.94	.67	1.22	.86	2.51	0.00
	Rigid	.07	.00	.00	.91	.30	.78	1.00	.10	1.55	1.54	1.35	1.19	4.70	0.00
	GVW	12.0	2.4	4.3	36.4	17.1	34.7	51.2	19.8	58.5	72.9	47.8	63.5	114.6	0.0
S Lane1	Num	9	1,172	623	11	73	307	3	55	116	9	2	3	3	0
	Flex	.04	.00	.00	.71	.31	.57	.34	.10	1.13	.80	1.52	.67	.79	0.00
	Rigid	.09	.00	.00	.94	.31	1.10	.88	.12	2.01	1.84	1.47	.97	1.56	0.00
	GVW	15.0	2.6	4.4	36.2	17.8	38.1	49.8	21.3	63.9	72.3	60.1	61.0	85.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Sep-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9