

Idaho Transportation Department

Monthly WIM Distribution for Oct-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	12	2,249	1,211	26	130	592	6	99	193	18	1	5	4	0
	Flex	.04	.00	.00	.78	.32	.52	.39	.13	1.09	.70	1.80	.89	1.39	0.00
	Rigid	.09	.00	.00	1.06	.32	.98	.91	.14	1.86	1.58	2.35	1.21	2.66	0.00
	GVW	13.8	2.5	4.4	38.5	17.9	37.4	50.8	22.4	62.6	71.0	48.1	64.4	97.7	0.0
N	Num	4	1,052	539	9	43	263	2	33	72	9	1	2	2	0
	Flex	.03	.00	.00	.61	.20	.42	.29	.10	.90	.63	.22	.97	1.67	0.00
	Rigid	.07	.00	.00	.85	.20	.78	.77	.11	1.52	1.44	.39	1.32	3.27	0.00
	GVW	11.2	2.4	4.2	36.2	16.0	35.4	48.8	20.8	58.7	69.8	31.5	66.8	107.8	0.0
S	Num	8	1,197	672	17	87	329	4	66	122	9	1	3	3	0
	Flex	.05	.00	.00	.86	.38	.59	.44	.14	1.21	.82	2.17	.86	1.20	0.00
	Rigid	.09	.00	.00	1.16	.39	1.13	.95	.16	2.06	1.83	3.14	1.16	2.31	0.00
	GVW	14.9	2.6	4.6	39.7	18.9	39.0	51.3	23.2	64.9	72.7	59.3	63.0	93.2	0.0
N Lane1	Num	4	1,052	539	9	43	263	2	33	72	9	1	2	2	0
	Flex	.03	.00	.00	.61	.20	.42	.29	.10	.90	.63	.22	.97	1.67	0.00
	Rigid	.07	.00	.00	.85	.20	.78	.77	.11	1.52	1.44	.39	1.32	3.27	0.00
	GVW	11.2	2.4	4.2	36.2	16.0	35.4	48.8	20.8	58.7	69.8	31.5	66.8	107.8	0.0
S Lane1	Num	8	1,197	672	17	87	329	4	66	122	9	1	3	3	0
	Flex	.05	.00	.00	.86	.38	.59	.44	.14	1.21	.82	2.17	.86	1.20	0.00
	Rigid	.09	.00	.00	1.16	.39	1.13	.95	.16	2.06	1.83	3.14	1.16	2.31	0.00
	GVW	14.9	2.6	4.6	39.7	18.9	39.0	51.3	23.2	64.9	72.7	59.3	63.0	93.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9