

Idaho Transportation Department

Monthly WIM Distribution for Nov-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	10	2,034	1,088	22	107	582	5	82	177	24	1	4	5	0
	Flex	.07	.00	.00	.73	.19	.53	.30	.11	1.07	.62	.55	.91	1.65	0.00
	Rigid	.14	.00	.00	.98	.19	.99	.71	.12	1.81	1.45	.79	1.25	3.61	0.00
	GVW	14.3	2.5	4.2	37.5	16.6	37.9	46.4	21.7	62.5	72.0	44.5	67.1	104.3	0.0
N	Num	4	995	500	8	40	250	3	28	70	13	1	2	2	0
	Flex	.03	.00	.00	.53	.16	.42	.24	.09	.87	.49	.13	1.13	2.87	0.00
	Rigid	.06	.00	.00	.71	.15	.76	.58	.10	1.45	1.14	.12	1.41	6.17	0.00
	GVW	12.1	2.4	4.0	34.4	15.6	35.8	45.4	20.5	58.5	68.3	25.2	71.9	120.3	0.0
S	Num	7	1,039	587	14	67	332	3	54	107	11	1	2	3	0
	Flex	.08	.00	.00	.83	.21	.61	.30	.12	1.19	.79	.72	.72	1.03	0.00
	Rigid	.17	.00	.00	1.10	.21	1.17	.73	.13	2.04	1.84	.97	1.02	2.44	0.00
	GVW	15.3	2.5	4.3	38.6	17.2	39.5	46.2	22.3	65.1	75.9	46.7	62.6	97.9	0.0
N Lane1	Num	4	995	500	8	40	250	3	28	70	13	1	2	2	0
	Flex	.03	.00	.00	.53	.16	.42	.24	.09	.87	.49	.13	1.13	2.87	0.00
	Rigid	.06	.00	.00	.71	.15	.76	.58	.10	1.45	1.14	.12	1.41	6.17	0.00
	GVW	12.1	2.4	4.0	34.4	15.6	35.8	45.4	20.5	58.5	68.3	25.2	71.9	120.3	0.0
S Lane1	Num	7	1,039	587	14	67	332	3	54	107	11	1	2	3	0
	Flex	.08	.00	.00	.83	.21	.61	.30	.12	1.19	.79	.72	.72	1.03	0.00
	Rigid	.17	.00	.00	1.10	.21	1.17	.73	.13	2.04	1.84	.97	1.02	2.44	0.00
	GVW	15.3	2.5	4.3	38.6	17.2	39.5	46.2	22.3	65.1	75.9	46.7	62.6	97.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9