

Idaho Transportation Department

Monthly WIM Distribution for Jan-2024

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	9	1,351	753	15	69	540	4	45	151	16	1	3	4	0
	Flex	.07	.00	.00	.70	.16	.56	.29	.14	1.21	.66	1.29	1.17	1.40	0.00
	Rigid	.15	.00	.00	.99	.16	1.06	.73	.17	2.01	1.53	1.28	1.71	3.13	0.00
	GVW	14.9	2.6	4.2	37.7	15.6	38.6	46.7	23.9	64.9	73.7	52.1	72.7	101.7	0.0
N	Num	4	672	360	7	28	237	2	20	65	9	1	2	2	0
	Flex	.08	.00	.00	.59	.16	.49	.30	.13	.95	.59	.93	1.35	1.37	0.00
	Rigid	.16	.00	.00	.85	.16	.92	.86	.15	1.61	1.36	.98	1.91	2.92	0.00
	GVW	14.9	2.6	4.2	36.4	15.4	37.4	49.3	23.9	60.4	71.7	50.7	76.8	106.3	0.0
S	Num	5	679	393	8	41	303	3	26	86	7	1	2	2	0
	Flex	.07	.00	.00	.78	.16	.61	.29	.16	1.42	.72	2.18	.93	1.30	0.00
	Rigid	.14	.00	.00	1.08	.16	1.17	.68	.19	2.32	1.66	2.23	1.36	3.22	0.00
	GVW	15.2	2.6	4.2	38.5	15.8	39.5	46.0	23.9	68.3	74.4	57.5	65.9	96.8	0.0
N Lane1	Num	4	672	360	7	28	237	2	20	65	9	1	2	2	0
	Flex	.08	.00	.00	.59	.16	.49	.30	.13	.95	.59	.93	1.35	1.37	0.00
	Rigid	.16	.00	.00	.85	.16	.92	.86	.15	1.61	1.36	.98	1.91	2.92	0.00
	GVW	14.9	2.6	4.2	36.4	15.4	37.4	49.3	23.9	60.4	71.7	50.7	76.8	106.3	0.0
S Lane1	Num	5	679	393	8	41	303	3	26	86	7	1	2	2	0
	Flex	.07	.00	.00	.78	.16	.61	.29	.16	1.42	.72	2.18	.93	1.30	0.00
	Rigid	.14	.00	.00	1.08	.16	1.17	.68	.19	2.32	1.66	2.23	1.36	3.22	0.00
	GVW	15.2	2.6	4.2	38.5	15.8	39.5	46.0	23.9	68.3	74.4	57.5	65.9	96.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2024

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9