

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2024

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	13	2,034	1,038	19	121	601	7	94	190	18	1	5	5	0
	Flex	.09	.01	.00	1.00	.33	.55	.33	.11	1.16	.78	1.29	1.08	1.41	0.00
	Rigid	.19	.01	.00	1.34	.34	1.05	.83	.13	1.99	1.85	1.27	1.60	2.90	0.00
	GVW	14.5	2.6	4.5	40.0	18.2	38.1	49.6	21.8	63.6	77.6	59.7	66.8	102.4	0.0
N	Num	5	1,082	558	11	71	282	3	56	81	8	1	3	2	0
	Flex	.06	.00	.00	.97	.45	.51	.33	.12	1.18	.79	1.77	.96	1.86	0.00
	Rigid	.13	.00	.00	1.29	.46	.96	.83	.14	1.91	1.85	1.81	1.30	3.50	0.00
	GVW	12.8	2.6	4.7	40.7	19.8	37.0	48.4	21.7	61.1	75.1	65.8	59.9	110.2	0.0
S	Num	7	953	480	8	49	319	4	38	109	9	1	3	3	0
	Flex	.10	.01	.00	1.01	.17	.58	.35	.10	1.14	.77	1.30	1.16	1.23	0.00
	Rigid	.21	.01	.00	1.33	.17	1.11	.88	.12	2.06	1.82	1.25	1.81	2.61	0.00
	GVW	15.3	2.6	4.2	38.3	15.9	38.9	50.6	21.9	65.6	80.0	59.1	72.3	95.0	0.0
N Lane1	Num	5	1,082	558	11	71	282	3	56	81	8	1	3	2	0
	Flex	.06	.00	.00	.97	.45	.51	.33	.12	1.18	.79	1.77	.96	1.86	0.00
	Rigid	.13	.00	.00	1.29	.46	.96	.83	.14	1.91	1.85	1.81	1.30	3.50	0.00
	GVW	12.8	2.6	4.7	40.7	19.8	37.0	48.4	21.7	61.1	75.1	65.8	59.9	110.2	0.0
S Lane1	Num	7	953	480	8	49	319	4	38	109	9	1	3	3	0
	Flex	.10	.01	.00	1.01	.17	.58	.35	.10	1.14	.77	1.30	1.16	1.23	0.00
	Rigid	.21	.01	.00	1.33	.17	1.11	.88	.12	2.06	1.82	1.25	1.81	2.61	0.00
	GVW	15.3	2.6	4.2	38.3	15.9	38.9	50.6	21.9	65.6	80.0	59.1	72.3	95.0	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2024

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9