

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2015

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	13	4,636	2,796	73	301	55	14	30	210	149	3	2	46	0
	Flex	.00	.00	.00	.61	.15	.73	.39	.37	.96	.62	1.03	.44	.92	0.00
	Rigid	.00	.00	.00	.72	.15	1.02	.71	.40	1.60	1.29	1.10	.44	1.72	0.00
	GVW	2.3	3.8	6.0	24.3	14.9	30.6	45.8	28.1	53.5	66.2	45.9	48.5	73.2	0.0
E	Num	6	2,460	1,449	28	55	27	12	14	107	79	2	1	20	0
	Flex	.00	.00	.00	.14	.10	.17	.18	.17	.24	.16	.38	.40	.25	0.00
	Rigid	.00	.00	.00	.15	.10	.23	.34	.18	.39	.32	.36	.41	.47	0.00
	GVW	2.7	3.1	5.4	18.9	15.6	24.4	41.4	26.4	43.2	50.0	41.9	50.0	60.2	0.0
W	Num	8	2,177	1,348	44	246	28	3	16	103	70	2	1	27	0
	Flex	.00	.00	.00	.87	.16	1.38	.98	.50	1.71	1.18	1.41	.39	1.33	0.00
	Rigid	.00	.00	.00	1.03	.17	1.93	1.97	.55	2.85	2.47	1.52	.40	2.52	0.00
	GVW	1.9	4.6	6.8	27.4	14.7	37.4	59.1	29.1	64.0	85.7	50.7	46.2	82.1	0.0
E Lane1	Num	6	2,460	1,449	28	55	27	12	14	107	79	2	1	20	0
	Flex	.00	.00	.00	.14	.10	.17	.18	.17	.24	.16	.38	.40	.25	0.00
	Rigid	.00	.00	.00	.15	.10	.23	.34	.18	.39	.32	.36	.41	.47	0.00
	GVW	2.7	3.1	5.4	18.9	15.6	24.4	41.4	26.4	43.2	50.0	41.9	50.0	60.2	0.0
W Lane1	Num	8	2,177	1,348	44	246	28	3	16	103	70	2	1	27	0
	Flex	.00	.00	.00	.87	.16	1.38	.98	.50	1.71	1.18	1.41	.39	1.33	0.00
	Rigid	.00	.00	.00	1.03	.17	1.93	1.97	.55	2.85	2.47	1.52	.40	2.52	0.00
	GVW	1.9	4.6	6.8	27.4	14.7	37.4	59.1	29.1	64.0	85.7	50.7	46.2	82.1	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2015

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9