

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2017

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	8	5,027	3,296	67	222	68	16	34	219	168	1	2	40	0
	Flex	.00	.00	.00	.30	.11	.31	.40	.25	.51	.36	.53	.46	.45	0.00
	Rigid	.00	.00	.00	.32	.11	.46	.61	.28	.85	.83	.51	.49	.83	0.00
	GVW	2.2	3.8	6.3	21.7	15.2	29.0	47.9	29.1	49.8	65.4	45.1	51.1	63.7	0.0
E	Num	4	2,546	1,650	29	96	26	14	19	111	75	1	1	16	0
	Flex	.00	.00	.00	.24	.11	.31	.41	.29	.38	.27	.48	.63	.33	0.00
	Rigid	.00	.00	.00	.25	.11	.44	.59	.33	.61	.50	.45	.66	.60	0.00
	GVW	2.3	3.7	6.3	20.9	15.7	28.2	47.9	30.9	46.6	50.5	45.9	58.3	58.7	0.0
W	Num	5	2,480	1,646	38	126	42	3	15	109	93	1	2	25	0
	Flex	.00	.00	.00	.35	.11	.32	.36	.20	.63	.43	.48	.23	.52	0.00
	Rigid	.00	.00	.00	.37	.11	.50	.60	.22	1.08	1.09	.46	.27	.98	0.00
	GVW	2.0	3.9	6.3	22.3	14.7	29.7	46.4	27.2	52.8	77.7	43.8	41.5	66.8	0.0
E Lane1	Num	4	2,546	1,650	29	96	26	14	19	111	75	1	1	16	0
	Flex	.00	.00	.00	.24	.11	.31	.41	.29	.38	.27	.48	.63	.33	0.00
	Rigid	.00	.00	.00	.25	.11	.44	.59	.33	.61	.50	.45	.66	.60	0.00
	GVW	2.3	3.7	6.3	20.9	15.7	28.2	47.9	30.9	46.6	50.5	45.9	58.3	58.7	0.0
W Lane1	Num	5	2,480	1,646	38	126	42	3	15	109	93	1	2	25	0
	Flex	.00	.00	.00	.35	.11	.32	.36	.20	.63	.43	.48	.23	.52	0.00
	Rigid	.00	.00	.00	.37	.11	.50	.60	.22	1.08	1.09	.46	.27	.98	0.00
	GVW	2.0	3.9	6.3	22.3	14.7	29.7	46.4	27.2	52.8	77.7	43.8	41.5	66.8	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2017

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9