

Idaho Transportation Department

Monthly WIM Distribution for May-2017

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	27	5,583	3,547	79	279	97	22	38	247	178	2	3	43	0
	Flex	.00	.00	.00	.35	.12	.37	.40	.36	.54	.39	.78	.25	.48	0.00
	Rigid	.00	.00	.00	.39	.12	.56	.72	.42	.91	.87	.77	.27	.97	0.00
	GVW	3.0	3.8	6.4	23.0	15.5	30.5	48.5	29.7	50.0	65.8	47.9	43.8	67.0	0.0
E	Num	15	2,833	1,796	38	122	40	17	20	123	84	1	1	17	0
	Flex	.00	.00	.00	.33	.13	.38	.38	.37	.43	.31	.48	.51	.44	0.00
	Rigid	.00	.00	.00	.37	.13	.56	.67	.42	.71	.58	.45	.54	.89	0.00
	GVW	3.1	3.7	6.3	23.0	15.8	30.7	47.9	31.3	48.3	53.0	47.1	54.7	68.0	0.0
W	Num	13	2,750	1,751	41	158	57	7	18	123	93	1	2	27	0
	Flex	.00	.00	.00	.35	.12	.37	.43	.30	.64	.46	.96	.15	.51	0.00
	Rigid	.00	.00	.00	.40	.12	.57	.94	.34	1.08	1.14	.96	.15	1.03	0.00
	GVW	3.1	3.9	6.4	22.6	15.2	30.5	52.7	27.4	51.3	77.5	48.3	39.3	66.5	0.0
E Lane1	Num	15	2,833	1,796	38	122	40	17	20	123	84	1	1	17	0
	Flex	.00	.00	.00	.33	.13	.38	.38	.37	.43	.31	.48	.51	.44	0.00
	Rigid	.00	.00	.00	.37	.13	.56	.67	.42	.71	.58	.45	.54	.89	0.00
	GVW	3.1	3.7	6.3	23.0	15.8	30.7	47.9	31.3	48.3	53.0	47.1	54.7	68.0	0.0
W Lane1	Num	13	2,750	1,751	41	158	57	7	18	123	93	1	2	27	0
	Flex	.00	.00	.00	.35	.12	.37	.43	.30	.64	.46	.96	.15	.51	0.00
	Rigid	.00	.00	.00	.40	.12	.57	.94	.34	1.08	1.14	.96	.15	1.03	0.00
	GVW	3.1	3.9	6.4	22.6	15.2	30.5	52.7	27.4	51.3	77.5	48.3	39.3	66.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2017

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9