

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	110	6,674	3,994	77	273	169	30	34	198	142	2	2	31	0
	Flex	.00	.00	.00	.36	.18	.31	.25	.30	.51	.35	.59	.30	.52	0.00
	Rigid	.00	.00	.00	.42	.18	.49	.63	.34	.87	.78	.56	.34	1.09	0.00
	GVW	3.5	3.7	6.1	24.1	16.3	29.9	46.7	29.7	49.5	63.4	48.0	45.5	69.8	0.0
E	Num	57	3,392	2,029	38	127	82	21	19	96	63	1	1	11	0
	Flex	.00	.00	.00	.32	.19	.31	.22	.40	.46	.28	.67	.49	.53	0.00
	Rigid	.00	.00	.00	.37	.19	.49	.54	.46	.79	.54	.63	.53	1.13	0.00
	GVW	3.1	3.7	6.1	23.9	16.3	30.6	45.7	32.3	49.6	51.2	51.1	54.2	73.3	0.0
W	Num	53	3,281	1,966	39	153	87	9	16	101	79	1	2	21	0
	Flex	.00	.00	.00	.38	.13	.32	.35	.18	.54	.39	.78	.18	.53	0.00
	Rigid	.00	.00	.00	.45	.13	.50	.83	.20	.93	.95	.78	.18	1.11	0.00
	GVW	3.8	3.7	6.1	24.2	15.5	29.2	49.5	26.3	49.2	73.1	46.4	40.1	69.0	0.0
E Lane1	Num	57	3,392	2,029	38	127	82	21	19	96	63	1	1	11	0
	Flex	.00	.00	.00	.32	.19	.31	.22	.40	.46	.28	.67	.49	.53	0.00
	Rigid	.00	.00	.00	.37	.19	.49	.54	.46	.79	.54	.63	.53	1.13	0.00
	GVW	3.1	3.7	6.1	23.9	16.3	30.6	45.7	32.3	49.6	51.2	51.1	54.2	73.3	0.0
W Lane1	Num	53	3,281	1,966	39	153	87	9	16	101	79	1	2	21	0
	Flex	.00	.00	.00	.38	.13	.32	.35	.18	.54	.39	.78	.18	.53	0.00
	Rigid	.00	.00	.00	.45	.13	.50	.83	.20	.93	.95	.78	.18	1.11	0.00
	GVW	3.8	3.7	6.1	24.2	15.5	29.2	49.5	26.3	49.2	73.1	46.4	40.1	69.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9