

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2017

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	92	6,923	4,199	76	304	177	27	38	201	144	1	2	33	0
	Flex	.00	.00	.00	.35	.13	.33	.25	.34	.50	.34	.51	.19	.49	0.00
	Rigid	.00	.00	.00	.42	.13	.52	.62	.42	.84	.78	.48	.20	.98	0.00
	GVW	3.5	3.7	6.1	23.8	15.5	30.5	47.0	31.1	49.0	65.1	47.6	42.8	65.9	0.0
E	Num	47	3,517	2,149	37	142	83	18	20	99	65	1	1	10	0
	Flex	.00	.00	.00	.36	.13	.32	.22	.44	.48	.30	.69	.45	.41	0.00
	Rigid	.00	.00	.00	.42	.13	.49	.56	.52	.80	.58	.65	.49	.85	0.00
	GVW	3.3	3.7	6.1	23.9	15.5	30.3	46.0	32.6	49.6	53.3	52.3	54.7	64.2	0.0
W	Num	45	3,406	2,050	39	163	94	9	19	103	79	1	2	23	0
	Flex	.00	.00	.00	.34	.14	.35	.30	.21	.52	.36	.15	.16	.51	0.00
	Rigid	.00	.00	.00	.41	.14	.54	.72	.26	.87	.90	.14	.16	1.01	0.00
	GVW	3.7	3.7	6.2	23.8	15.6	30.7	49.0	28.3	48.2	73.0	36.0	40.5	66.2	0.0
E Lane1	Num	47	3,517	2,149	37	142	83	18	20	99	65	1	1	10	0
	Flex	.00	.00	.00	.36	.13	.32	.22	.44	.48	.30	.69	.45	.41	0.00
	Rigid	.00	.00	.00	.42	.13	.49	.56	.52	.80	.58	.65	.49	.85	0.00
	GVW	3.3	3.7	6.1	23.9	15.5	30.3	46.0	32.6	49.6	53.3	52.3	54.7	64.2	0.0
W Lane1	Num	45	3,406	2,050	39	163	94	9	19	103	79	1	2	23	0
	Flex	.00	.00	.00	.34	.14	.35	.30	.21	.52	.36	.15	.16	.51	0.00
	Rigid	.00	.00	.00	.41	.14	.54	.72	.26	.87	.90	.14	.16	1.01	0.00
	GVW	3.7	3.7	6.2	23.8	15.6	30.7	49.0	28.3	48.2	73.0	36.0	40.5	66.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2017

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9