

# Idaho Transportation Department

## Monthly WIM Distribution for Nov-2018

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	5,400	3,557	81	266	78	10	31	224	169	2	4	46	0
	Flex	.00	.00	.00	.26	.08	.38	.37	.30	.46	.32	.40	.40	.39	0.00
	Rigid	.00	.00	.00	.28	.08	.53	.67	.33	.75	.68	.38	.43	.77	0.00
	GVW	2.5	4.0	6.5	20.6	14.5	30.3	47.7	29.0	48.3	62.7	42.5	46.2	61.8	0.0
E	Num	2	2,703	1,735	36	176	31	8	17	112	79	1	2	19	0
	Flex	.00	.00	.00	.42	.08	.59	.58	.47	.60	.43	.55	.77	.60	0.00
	Rigid	.00	.00	.00	.44	.08	.81	1.08	.51	.96	.81	.52	.81	1.23	0.00
	GVW	2.6	4.3	6.9	23.7	14.3	34.1	55.3	33.6	51.9	58.8	49.3	60.0	75.0	0.0
W	Num	2	2,697	1,823	46	90	47	4	15	112	90	1	3	27	0
	Flex	.00	.00	.00	.15	.09	.24	.14	.14	.33	.23	.27	.12	.24	0.00
	Rigid	.00	.00	.00	.16	.09	.34	.36	.15	.55	.56	.26	.13	.47	0.00
	GVW	2.4	3.7	6.1	18.5	15.0	28.0	42.0	24.9	44.8	66.9	37.0	35.8	53.2	0.0
E Lane1	Num	2	2,703	1,735	36	176	31	8	17	112	79	1	2	19	0
	Flex	.00	.00	.00	.42	.08	.59	.58	.47	.60	.43	.55	.77	.60	0.00
	Rigid	.00	.00	.00	.44	.08	.81	1.08	.51	.96	.81	.52	.81	1.23	0.00
	GVW	2.6	4.3	6.9	23.7	14.3	34.1	55.3	33.6	51.9	58.8	49.3	60.0	75.0	0.0
W Lane1	Num	2	2,697	1,823	46	90	47	4	15	112	90	1	3	27	0
	Flex	.00	.00	.00	.15	.09	.24	.14	.14	.33	.23	.27	.12	.24	0.00
	Rigid	.00	.00	.00	.16	.09	.34	.36	.15	.55	.56	.26	.13	.47	0.00
	GVW	2.4	3.7	6.1	18.5	15.0	28.0	42.0	24.9	44.8	66.9	37.0	35.8	53.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Nov-2018

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9