

Idaho Transportation Department

Monthly WIM Distribution for Dec-2018

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	5,045	3,271	72	219	58	7	26	186	131	2	4	35	0
	Flex	.00	.00	.00	.24	.08	.42	.32	.26	.47	.33	.35	.46	.38	0.00
	Rigid	.00	.00	.00	.25	.07	.58	.68	.29	.75	.70	.33	.51	.71	0.00
	GVW	2.5	4.0	6.4	20.0	14.0	30.2	47.1	28.7	48.3	64.2	42.0	48.1	59.9	0.0
E	Num	2	2,554	1,629	33	148	24	6	14	93	65	1	2	14	0
	Flex	.00	.00	.00	.38	.07	.67	.39	.39	.61	.45	.45	.74	.65	0.00
	Rigid	.00	.00	.00	.40	.07	.92	.81	.44	.97	.86	.43	.81	1.22	0.00
	GVW	2.4	4.3	6.8	22.9	13.8	34.0	47.8	32.3	52.3	61.0	47.7	60.2	75.0	0.0
W	Num	2	2,491	1,642	41	71	34	2	13	93	70	1	2	22	0
	Flex	.00	.00	.00	.13	.08	.25	.24	.13	.32	.24	.27	.13	.25	0.00
	Rigid	.00	.00	.00	.13	.08	.34	.46	.15	.53	.58	.25	.14	.46	0.00
	GVW	2.3	3.8	6.0	17.4	14.6	27.7	44.1	25.2	44.2	67.0	37.2	37.7	52.5	0.0
E Lane1	Num	2	2,554	1,629	33	148	24	6	14	93	65	1	2	14	0
	Flex	.00	.00	.00	.38	.07	.67	.39	.39	.61	.45	.45	.74	.65	0.00
	Rigid	.00	.00	.00	.40	.07	.92	.81	.44	.97	.86	.43	.81	1.22	0.00
	GVW	2.4	4.3	6.8	22.9	13.8	34.0	47.8	32.3	52.3	61.0	47.7	60.2	75.0	0.0
W Lane1	Num	2	2,491	1,642	41	71	34	2	13	93	70	1	2	22	0
	Flex	.00	.00	.00	.13	.08	.25	.24	.13	.32	.24	.27	.13	.25	0.00
	Rigid	.00	.00	.00	.13	.08	.34	.46	.15	.53	.58	.25	.14	.46	0.00
	GVW	2.3	3.8	6.0	17.4	14.6	27.7	44.1	25.2	44.2	67.0	37.2	37.7	52.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2018

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9