

Idaho Transportation Department

Monthly WIM Distribution for Feb-2019

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	4,376	3,135	73	250	37	8	25	171	132	2	3	35	0
	Flex	.00	.00	.00	.25	.11	.42	.36	.34	.55	.40	.31	.65	.50	0.00
	Rigid	.00	.00	.00	.28	.11	.61	.75	.40	.92	.81	.29	.75	.87	0.00
	GVW	2.9	4.1	6.3	20.6	13.8	30.9	47.1	28.9	51.2	65.6	41.0	52.1	64.3	0.0
E	Num	2	2,150	1,575	36	183	12	6	12	79	52	1	1	11	0
	Flex	.00	.00	.00	.38	.12	.77	.54	.58	.80	.58	.43	1.11	1.01	0.00
	Rigid	.00	.00	.00	.43	.13	1.14	1.04	.69	1.32	1.05	.40	1.25	1.72	0.00
	GVW	2.6	4.4	6.7	23.8	13.7	37.2	52.2	32.3	57.1	60.9	46.4	66.3	80.5	0.0
W	Num	1	2,226	1,560	37	68	26	2	14	92	80	2	2	24	0
	Flex	.00	.00	.00	.12	.08	.26	.14	.15	.34	.29	.28	.09	.29	0.00
	Rigid	.00	.00	.00	.12	.08	.35	.33	.17	.57	.68	.27	.10	.54	0.00
	GVW	3.2	3.7	6.0	17.3	14.2	28.1	40.0	26.5	46.1	69.3	39.9	37.0	58.0	0.0
E Lane1	Num	2	2,150	1,575	36	183	12	6	12	79	52	1	1	11	0
	Flex	.00	.00	.00	.38	.12	.77	.54	.58	.80	.58	.43	1.11	1.01	0.00
	Rigid	.00	.00	.00	.43	.13	1.14	1.04	.69	1.32	1.05	.40	1.25	1.72	0.00
	GVW	2.6	4.4	6.7	23.8	13.7	37.2	52.2	32.3	57.1	60.9	46.4	66.3	80.5	0.0
W Lane1	Num	1	2,226	1,560	37	68	26	2	14	92	80	2	2	24	0
	Flex	.00	.00	.00	.12	.08	.26	.14	.15	.34	.29	.28	.09	.29	0.00
	Rigid	.00	.00	.00	.12	.08	.35	.33	.17	.57	.68	.27	.10	.54	0.00
	GVW	3.2	3.7	6.0	17.3	14.2	28.1	40.0	26.5	46.1	69.3	39.9	37.0	58.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2019

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9