

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2019

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	7	4,973	3,352	61	292	37	2	23	162	119	1	3	27	0
	Flex	.00	.00	.00	.29	.08	.37	.36	.30	.58	.43	.74	.55	.50	0.00
	Rigid	.00	.00	.00	.30	.08	.50	.66	.32	.96	.87	.70	.66	.99	0.00
	GVW	2.4	4.0	6.5	21.1	13.8	28.8	46.9	28.0	50.6	63.4	49.6	47.1	67.9	0.0
E	Num	4	2,459	1,663	29	215	16	2	11	77	58	1	2	10	0
	Flex	.00	.00	.00	.44	.07	.53	.47	.44	.75	.58	.90	1.06	.66	0.00
	Rigid	.00	.00	.00	.47	.07	.71	.81	.47	1.22	1.02	.86	1.21	1.19	0.00
	GVW	2.4	4.3	6.9	24.3	13.4	32.7	49.4	31.8	54.6	57.8	53.3	62.4	69.5	0.0
W	Num	4	2,515	1,689	32	77	21	1	12	85	61	1	2	16	0
	Flex	.00	.00	.00	.16	.10	.26	.14	.14	.42	.33	.11	.12	.41	0.00
	Rigid	.00	.00	.00	.17	.09	.35	.43	.14	.71	.81	.12	.12	.90	0.00
	GVW	2.4	3.8	6.1	18.6	14.7	26.2	44.1	23.8	46.6	70.6	31.1	37.1	68.1	0.0
E Lane1	Num	4	2,459	1,663	29	215	16	2	11	77	58	1	2	10	0
	Flex	.00	.00	.00	.44	.07	.53	.47	.44	.75	.58	.90	1.06	.66	0.00
	Rigid	.00	.00	.00	.47	.07	.71	.81	.47	1.22	1.02	.86	1.21	1.19	0.00
	GVW	2.4	4.3	6.9	24.3	13.4	32.7	49.4	31.8	54.6	57.8	53.3	62.4	69.5	0.0
W Lane1	Num	4	2,515	1,689	32	77	21	1	12	85	61	1	2	16	0
	Flex	.00	.00	.00	.16	.10	.26	.14	.14	.42	.33	.11	.12	.41	0.00
	Rigid	.00	.00	.00	.17	.09	.35	.43	.14	.71	.81	.12	.12	.90	0.00
	GVW	2.4	3.8	6.1	18.6	14.7	26.2	44.1	23.8	46.6	70.6	31.1	37.1	68.1	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2019

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9