

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2019

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	11	5,634	3,883	83	338	74	18	35	211	193	2	4	41	0
	Flex	.00	.00	.00	.33	.08	.36	.65	.34	.56	.40	.69	.37	.46	0.00
	Rigid	.00	.00	.00	.35	.08	.52	1.05	.37	.90	.84	.67	.40	.93	0.00
	GVW	2.3	4.0	6.6	21.8	14.6	29.4	53.3	28.5	49.4	65.2	46.8	44.9	65.8	0.0
E	Num	7	2,817	1,926	39	236	30	14	19	104	95	1	2	18	0
	Flex	.00	.00	.00	.46	.08	.54	.85	.48	.73	.52	.76	.96	.67	0.00
	Rigid	.00	.00	.00	.50	.08	.77	1.36	.52	1.16	.97	.73	1.03	1.33	0.00
	GVW	2.5	4.3	7.0	24.6	14.5	33.2	57.5	31.5	53.9	58.7	52.9	65.1	74.7	0.0
W	Num	5	2,817	1,957	44	102	45	4	16	107	97	1	3	23	0
	Flex	.00	.00	.00	.21	.09	.24	.34	.16	.39	.28	.55	.09	.32	0.00
	Rigid	.00	.00	.00	.21	.09	.35	.56	.16	.65	.73	.53	.10	.65	0.00
	GVW	2.0	3.7	6.2	19.2	15.0	27.1	48.1	24.5	45.0	72.4	41.8	35.4	59.5	0.0
E Lane1	Num	7	2,817	1,926	39	236	30	14	19	104	95	1	2	18	0
	Flex	.00	.00	.00	.46	.08	.54	.85	.48	.73	.52	.76	.96	.67	0.00
	Rigid	.00	.00	.00	.50	.08	.77	1.36	.52	1.16	.97	.73	1.03	1.33	0.00
	GVW	2.5	4.3	7.0	24.6	14.5	33.2	57.5	31.5	53.9	58.7	52.9	65.1	74.7	0.0
W Lane1	Num	5	2,817	1,957	44	102	45	4	16	107	97	1	3	23	0
	Flex	.00	.00	.00	.21	.09	.24	.34	.16	.39	.28	.55	.09	.32	0.00
	Rigid	.00	.00	.00	.21	.09	.35	.56	.16	.65	.73	.53	.10	.65	0.00
	GVW	2.0	3.7	6.2	19.2	15.0	27.1	48.1	24.5	45.0	72.4	41.8	35.4	59.5	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2019

Site names: 00241  
 County: Kootenai  
 Funct Class: R Principal Arterial - Other  
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9