

Idaho Transportation Department

Monthly WIM Distribution for Jul-2019

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	34	7,514	4,872	79	392	96	16	40	239	169	2	4	56	0
	Flex	.00	.00	.00	.35	.11	.44	.37	.40	.57	.40	.51	.35	.56	0.00
	Rigid	.00	.00	.00	.41	.11	.68	.84	.46	.95	.88	.49	.37	1.04	0.00
	GVW	1.6	4.0	6.5	23.2	15.5	30.9	50.5	28.4	49.5	65.8	44.7	43.3	63.8	0.0
E	Num	18	3,737	2,529	40	242	37	10	22	117	79	1	2	23	0
	Flex	.00	.00	.00	.44	.10	.61	.37	.55	.71	.50	.91	.86	.88	0.00
	Rigid	.00	.00	.00	.52	.10	.93	.91	.65	1.20	1.01	.87	.90	1.69	0.00
	GVW	1.6	4.2	6.8	25.2	15.3	34.0	51.9	31.0	55.0	61.6	52.8	59.2	79.7	0.0
W	Num	16	3,777	2,343	39	149	59	7	18	122	90	1	3	33	0
	Flex	.00	.00	.00	.25	.13	.35	.32	.21	.43	.32	.25	.28	.38	0.00
	Rigid	.00	.00	.00	.29	.13	.53	.67	.24	.71	.79	.23	.29	.69	0.00
	GVW	1.6	3.8	6.2	21.1	15.9	29.0	48.5	25.1	44.4	70.4	39.3	40.8	55.7	0.0
E Lane1	Num	18	3,737	2,529	40	242	37	10	22	117	79	1	2	23	0
	Flex	.00	.00	.00	.44	.10	.61	.37	.55	.71	.50	.91	.86	.88	0.00
	Rigid	.00	.00	.00	.52	.10	.93	.91	.65	1.20	1.01	.87	.90	1.69	0.00
	GVW	1.6	4.2	6.8	25.2	15.3	34.0	51.9	31.0	55.0	61.6	52.8	59.2	79.7	0.0
W Lane1	Num	16	3,777	2,343	39	149	59	7	18	122	90	1	3	33	0
	Flex	.00	.00	.00	.25	.13	.35	.32	.21	.43	.32	.25	.28	.38	0.00
	Rigid	.00	.00	.00	.29	.13	.53	.67	.24	.71	.79	.23	.29	.69	0.00
	GVW	1.6	3.8	6.2	21.1	15.9	29.0	48.5	25.1	44.4	70.4	39.3	40.8	55.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2019

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9